

## 40 CDK - MODULAR WATERTIGHT ENCLOSURES AND DISTRIBUTION BOARDS - IP65

	 EN 62262	 EN 60529	 EN 60695-2-11	 EN 61140
--	--------------	--------------	-------------------	--------------

## SMOKED TRANSPARENT DOOR - SMOOTH WALLS

GW40101



## ENCLOSURES - PRE-ARRANGED FOR TERMINAL BLOCK - GREY RAL 7035



Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Installable terminal blocks	Dispersible power (W)	Pack Carton
GW 40 101	4	143x210x100		13	19
GW 40 102	8	215x210x100	1xGW40401	16	12
GW 40 103	12	298x260x140	1xGW40402	26	6
GW 40 106	18	410x285x140	1xGW40404	38	3

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels.

NOTES: dispersible power calculated according to IEC 60670-24. For the perforations, use the GW52401 milling cutter.

To restore the doubleinsulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).

For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.

CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.

GW40105

DISTRIBUTION BOARDS WITH PANELS WITH WINDOW AND EXTRACTABLE FRAME  
PROVISION FOR TERMINAL BLOCK - GREY RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Installable terminal blocks	Dispersible power (W)	Pack Carton
GW 40 104	24 (12x2)	298x420x140	1xGW40402	32	3
GW 40 105	36 (12x3)	298x570x140	2xGW40402	42	2
GW 40 107	36 (18x2)	410x463x140	2xGW40404	43	2
GW 40 108	54 (18x3)	410x655x140	2xGW40404	66	1
GW 40 109	72 (18x4)	410x878x160	4xGW40404	89	1

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels.

NOTES: dispersible power calculated according to IEC 60670-24. For the perforations, use the GW52401 milling cutter.

To restore the doubleinsulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).

For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.

CHARACTERISTICS: removable, sealing panels with windows. Thermo-pressure with ball equal to 70°C.