

SURFACE-MOUNTING BOXES IN GWPLAST 75 - GWT 650°C - FOR ORDINARY JUNCTIONS

	 EN 62262	 EN 60695-2-11	 EN 60695-10-2	 EN 61140
--	--------------	-------------------	-------------------	--------------

WALLS WITH CABLE GLANDS - IP44 AND IP55

GW44001



JUNCTION BOXES WITH PLAIN PRESS-ON LID - IP44 - GREY RAL 7035

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 44 001	Ø 65x35	4 / 23	5/280
GW 44 002	Ø 80x40	4 / 23	5/135
GW 44 003	80x80x40	6 / 23	5/90

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material.

GW44024



JUNCTION BOXES WITH PLAIN QUICK FIXING LID - IP55 - GREY RAL 7035

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Type	Pack Carton
GW 44 024	100x100x50	6 / 29	4 insul. a 1/4 turn	Quick entry	66
GW 44 026	150x110x70	10 / 29	4 insul. a 1/4 turn	Quick entry	40

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material, or the brackets for wall mounting.

GW44024 and GW44026 will be provided with quick entry cable glands from March 2013.

Cable gland suitable for cables from 4 to 14 mm and conduits ø 16, 20 and 25 mm.

GW44007



JUNCTION BOXES WITH PLAIN SCREWED LID - IP55 - GREY RAL 7035

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Type	Pack Carton
GW 44 004	100x100x50	6 / 29	4 - Stainless steel	Quick entry	66
GW 44 005	120x80x50	6 / 29	4 - Stainless steel	Quick entry	66
GW 44 006	150x110x70	10 / 29	4 - Stainless steel	Quick entry	40
GW 44 007	190x140x70	10 / 37	4 insul. sealable hinged		24
GW 44 008	240x190x90	12 / 37	4 insul. sealable hinged		12
GW 44 009	300x220x120	12 / 48	4 insul. sealable hinged		6
GW 44 010	380x300x120	12 / 48	4 insul. sealable hinged		4
GW 44 011	460x380x120	14 / 48	6 insul. sealable hinged		3

ACCESSORIES SUPPLIED: GW44011, screwcaps for double insulation.

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material, or the brackets for wall mounting.

GW44004, GW44005 and GW44006 will be provided with quick entry cable glands from March 2013.

Cable gland suitable for cables from 4 to 14 mm and conduits ø 16, 20 and 25 mm.