

SURFACE-MOUNTING ROTARY SWITCHES IN ISOLATING MATERIAL - IP65

COMMAND VERSIONS

GW70401



ROTARY SURFACE-MOUNTING SWITCHES - COMMAND VERSION WITH LOCKABLE BLACK KNOB - IP65

Code	No. of poles	Outer dim. LxHxD (mm)	Pack Carton
RATED CURRENT (A): 16			
GW 70 401	2	114x114x71.5	1/16
GW 70 402	3	114x114x71.5	1/16
GW 70 403	4	114x114x71.5	1/16
RATED CURRENT (A): 32			
GW 70 404	2	114x114x71.5	1/16
GW 70 405	3	114x114x71.5	1/16
GW 70 406	4	114x114x71.5	1/16
RATED CURRENT (A): 40			
GW 70 413	2	114x114x71.5	1/16
GW 70 414	3	114x114x71.5	1/16
GW 70 415	4	114x114x71.5	1/16
RATED CURRENT (A): 63			
GW 70 407	3	170x170x96	1/6
GW 70 408	4	170x170x96	1/6

NOTES: Can be padlocked with 3 locks in the OFF position and one in the ON position.

EMERGENCY VERSIONS

GW70432



SURFACE MOUNTING INSULATING ROTARY SWITCHES, EMERGENCY VERSION WITH LOCKABLE RED KNOB ON YELLOW FLANGE - IP65

Code	No. of poles	Outer dim. LxHxD (mm)	Pack Carton
RATED CURRENT (A): 16			
GW 70 431	2	114x114x71.5	1/16
GW 70 432	3	114x114x71.5	1/16
GW 70 433	4	114x114x71.5	1/16
RATED CURRENT (A): 32			
GW 70 434	2	114x114x71.5	1/16
GW 70 435	3	114x114x71.5	1/16
GW 70 436	4	114x114x71.5	1/16
RATED CURRENT (A): 40			
GW 70 441	2	114x114x71.5	1/16
GW 70 442	3	114x114x71.5	1/16
GW 70 443	4	114x114x71.5	1/16
RATED CURRENT (A): 63			
GW 70 437	3	170x170x96	1/6
GW 70 438	4	170x170x96	1/6

ACCESSORIES SUPPLIED: GW44622 screwcaps.

NOTES: Can be padlocked with 3 locks in the OFF position.