

HDC enclosures HDC 48B TSLU 1PG29G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Type	HDC 48B TSLU 1PG29G
Order No.	1650850000
Version	HDC enclosures, Size: 12, Protection degree: IP 65, Cable entry from side, Plug housing, End-locking clamp, lower side, Standard, Size of cable entries: PG 29
GTIN (EAN)	4008190299453
Qty.	1 pc(s).

HDC enclosures HDC 48B TSLU 1PG29G

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	151 mm	Width	90 mm
Height	94 mm	Net weight	726 g

Dimensions

Total length housing	132 mm	Width housing C	90 mm
Height of housing B	94 mm	Cable entry	w. threading

General data

Housing main material	diecast aluminium
-----------------------	-------------------

Version

Internal thread	PG 29	Design of housing	Cable entry from side, Plug housing
Size	12	Design	Standard
Top part/bottom part/lid	upper part	Design of locking system	End-locking clamp, lower side
Cable entry	w. threading	Size of cable entries	PG 29
Number of cable entry on top	0	Number of cable entry sideways	1

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

Approvals

Approvals



ROHS Conform

Downloads

PDF	1650850000_HDC_48B_TSLU_1PG29G_STP_Blatt_1.pdf
IGES	1650850000_HDC_48B_TSLU_1PG29G_STP.igs
VRML	1650850000_HDC_48B_TSLU_1PG29G_STP.wrl
EPLAN	1650850000.MZF
	3-D model

Data sheet...

**HDC enclosures
HDC 48B TSLU 1PG29G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

