



Commercial & Industrial Lighting

Spectrum



The Spectrum offers an attractive range of surface mounted luminaires with a multitude of applications.

Applications

- Reception Areas
- Commercial Offices
- Schools
- Meeting Rooms
- Corridors
- Leisure Centres
- Community Centres

Standard Features

- Fitted With A Reeded Acrylic Wrap Around Frosted Prismatic Diffuser For Even Light Distribution.
- Attractive Design And Slim Profile Neatly Blends Into The Installation
- Diffuser Held Captive Within The End Caps For Positive Fixing.

Spectrum Downloads

[Download PDF Datasheet](#)

Specification Guide


T5



Order Code	Watt	L	W	KgInfo
SPE128/HF/X	1 x 28W	1293	208	5.5
SPE135/HF/X	1 x 35W	1593	208	7.2
SPE149/HF/X	1 x 49W	1593	208	7.2
SPE228/HF/X	2 x 28W	1293	208	6.4
SPE235/HF/X	2 x 35W	1593	208	8.1
SPE249/HF/X	2 x 49W	1593	208	8.1

T8



Order Code	Watt	L	W	KgInfo
SPE218/X	2 x 18W	693	208	4.2 
SPE236/X	2 x 36W	1293	208	6.4 
SPE258/X	2 x 58W	1593	208	

To Order Features

(Add suffix to order code)

/840: Colour 840 Lamps

/AD: Analogue Dimmable Gear

/CONT: Continuation of Run

/DD: DSI Dimmable Gear

/DL: DALI Dimmable Gear

/END: End of Run

/FTB: Fused Terminal Block

/HF: High Frequency

/M3: 3hr Emergency Converted

/SD: Switch Dimmable Gear

/START: Start of Run

/SUSP: Pendant Suspension Kit

Example order code:

SPE235/HF/X – A 2X35W Spectrum luminaire with H/F gear, frosted diffuser and excluding lamps.

Note: All dimensions are in millimetres.

Main Line: **01208 79524** Fax: **01208 72832** Email: info@fitzlight.co.uk