


## SHARK 325W

Gel insulated join



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material</b>	Polyamide
<b>Filling</b>	Silicone
<b>Temp. range min</b>	-20 °C
<b>Temp. range max</b>	90 °C
<b>Glow wire test</b>	self-extinguishing
<b>Voltage</b>	0,6 kV - 1 kV
<b>Quantity of cable</b>	3
<b>Order no. UK</b>	SH325W
<b>Type</b>	SHARK 325W
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC001169

Remarks:

Ampere: 6

Cable Size: 3 core

LxBxH: 47x86x27 mm

Description:

SHARK SMARTSHARK Pre-filled gel insulated straight joint. Includes 3 pole terminal block.

Additional Info:

Ready to use, re-enterable, no mixing or pouring, immediate operation, excellent electrical insulation, good mechanical strenght, no expiry date.

24.04.2018

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com