

wiring devices | surface

www.mkelectric.co.uk

Switchsocket Outlets

13 AMP

SURFACE

WITH OUTBOARD ROCKERS 13 AMP

SURFACE

WITH NEONS 13 AMP

SURFACE

13 AMP SOCKET 20 AMP SWITCH

KEY OPERATED











K2977ALM 1 GANG DP WITH DUAL EARTH TERMINALS

K2977D5ALM 1 GANG DP WITH DUAL EARTH TERMINALS WITHOUT BOX

K2977D6ALM

1 GANG DP WITH RED ROCKER
AND DUAL EARTH TERMINALS

K2946ALM 2 GANG DP

X2946D5ALM 2 GANG DP WITHOUT BOX X2946D6ALM

K2946D6ALM 2 GANG DP WITH RED ROCKERS

Earth terminal fitted in boxes.

DIMENSIONS:
1 gang: 86 x 86 x 51mm
2 gang: 86 x 146 x 51mm
TERMINAL CAPACITY:
2 x 6 mm² stranded (max)
KNOCKOUTS: 1 gang: 6 x 20mm.
Two in one side and one in each of the other three sides. One in base
2 gang: 8 x 20mm.
Three in top two in bottom sides and one in each end. One in base

SPARE BOXES:
1 gang: K829ALM* K899ALM
2 gang: K830ALM* K897ALM
(*without side knockouts)
All boxes have a base knockout.
Boxes: BS 5733: 2010
Socket: BS 1363 Pt.2: 1995

K3077WHI 1 GANG DP WITHOUT BOX

5

K3046WHI

2 GANG DP WITHOUT BOX

High integrity earthing

One gang switchsockets, two gang outboard switchsockets and two

gang unswitched sockets are fitted

with two earth terminals to provide a double earth facility for use when

installations require a high integrity

All switchsockets have double pole

protective connection as specified

within BS 7671: 2008.

breaks last).

Double pole switching

switching (neutral makes first,

K2945ALM
2 GANG DP
WITH OUTBOARD
ROCKERS AND DUAL
EARTH TERMINALS

10

5

K2945D5ALM 2 GANG DP WITH OUTBOARD ROCKERS AND DUAL EARTH TERMINALS WITHOUT BOX

K2945D6ALM 2 GANG DP WITH RED OUTBOARD ROCKERS AND DUAL EARTH TERMINALS

K3045WHI 2 GANG DP WITHOUT BOX WITH OUTBOARD ROCKERS AND DUAL EARTH TERMINALS 1 GANG DP WITH NEON AND DUAL EARTH TERMINALS

1

1

5

K2477D6ALM 1 GANG DP WITH NEON, RED ROCKER AND DUAL EARTH TERMINALS

2 GANG DP WITH NEONS K2446D6ALM

K2446ALM

2 GANG DP WITH NEONS AND RED ROCKERS K2435ALM DP KEY OPERATED SOCKET

Earth terminal fitted in boxes.

5

1

5

1

K5252ALM 5
20AX DP KEY OPERATED SWITCH

5

DIMENSIONS:

1 gang: 86 x 86 x 51mm

2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

1 x 6 mm² stranded (max)

KNOCKOUTS:

1 gang: 6 x 20mm.

Two in one side and one in each of the other three sides. One in base 2 gang: 8 x 20mm.

Three in top two in bottom sides and one in each end. One in base SPARE BOXES:

1 gang: K829ALM* K899ALM
2 gang: K830ALM* K897ALM

2 gang: K830ALM* K897ALM (*without side knockouts) All boxes have a base knockout.

Boxes: BS 5733: 2010 Socket: BS 1363 Pt.2: 1995 Switch: BS EN 60669-1: 1999