

Euro
Datacom
ModulesLU6C Data
FrontplatesLU6C Datacom
Modules

TELEPHONE

BNC

BLANKS

FRONTPLATES

RJ11/12

RJ45 CAT 6



K5820WHI



K5821WHI



K5821BLK



K5801WHI



K180WHI



K188WHI



K188BLK



K186WHI



K186BLK



K172ALM



K5787WHI



K5746WHI



K5746BLK



K5746sWHI



K5746sBLK

K5820WHI **5**
K5820BLK **5**
 TELEPHONE MASTER
 ONE MODULE 25 X 50MM

K5821WHI **5**
K5821BLK **5**
 TELEPHONE SECONDARY
 ONE MODULE 25 X 50MM

MOUNTING BOXES:
 Minimum depth 25mm
 BS 6312 Pt 2

K5801WHI **5**
 BNC 50Ω
 ONE MODULE 25 X 50MM

50 Ohm crimp connector
 suitable for use with
 RG58, URM43, URM76
 and Belden 9907 type
 co-axial cables.

MOUNTING BOXES:
 Minimum box depth
 25mm

K180WHI **10**
 TWO MODULE
 BLANK 50 X 50MM

K188WHI **10**
K188BLK **10**
 ONE MODULE
 BLANK 25 X 50MM

K186WHI **10**
K186BLK **10**
 HALF MODULE
 BLANK 12.5 X 50MM

MOUNTING BOXES:
 Minimum depth 16mm
 BS 5733: 2010 where
 applicable

K172ALM **10**
 1 GANG TWIN
 LU6C FRONTPLATE
 TWO MODULE
 APERTURE SIZE 22 X 37MM

MOUNTING BOXES:
 Suitable for flush boxes to
 BS 4662: 2006 and surface
 boxes to BS 5733: 2010
 Refer to appropriate module
 for minimum box depth.

FIXING CENTRES:
 1 gang: 60.3mm
 2 gang: 120.6mm

BS 5733: 2010 where
 appropriate

Note: No grid required,
 modules just clip into place

K5787WHI **5**
 RJ11/12
 ONE MODULE

Suitable for both RJ11 and
 RJ12 jacks.
 RJ11: 4 wire
 RJ12: 6 wire

MOUNTING BOXES:
 Minimum box depth 25mm
 FCC68
 EN41003

K5746WHI **5**
K5746BLK **5**
 RJ45 CAT 6
 ONE MODULE

K5746sWHI **5**
K5746sBLK **5**
 RJ45 CAT 6
 SCREENED
 ONE MODULE

Cat 6 performance.
 Suitable for both 568A and
 568B wiring schemes.

MOUNTING BOXES:
 Minimum Box Depth 35mm
 ISO/IEC 11801
 EN 50173
 TIA 568
 EN 41003