

**IP44
SPLASHPROOF
380 - 415V
50 - 60 Hz**

Plugs

Connectors

Socket Outlets
ANGLED

STRAIGHT

SURFACE

SURFACE – LOOP IN PANEL MOUNTING

Amps Pin.
Config-
uration Earth
Hour
Pos



16	2P+E	9
16	3P+E	6
16	3P+N+E	6
32	3P+E	6
32	3P+N+E	6
63	3P+E	6
63	3P+N+E	6

K9002RED
K9007RED
K9015RED
K9037RED
K9045RED
K9066RED
K9071RED

K9102RED
K9107RED
K9115RED
K9137RED
K9144RED
K9165RED
K9170RED

K9202RED
K9207RED
K9215RED
K9237RED
K9241RED
K9265RED
K9269RED

K13207RED
K13215RED
K13237RED
K13241RED

K9407RED
K9415RED
K9437RED
K9445RED
K9465RED
K9470RED

16A/32A Fitted with cable entry gland.

63A Fitted with cable entry gland.

Thread size M48.

16A/32A Fitted with cable entry gland.

63A Fitted with cable entry gland.

Thread size M48.

16A Top conduit (M20) or rear cable entry, complete with blanking plug.

32A Top conduit (M25) or rear cable entry, complete with blanking plug.

63A Top conduit (M32) or rear cable entry, complete with blanking plug.

Suitable for top entry 2 x Ø25.

Fitted with terminals for Loop In 2 x 10mm².

16/32A All flanges have the same fixing centres and outside dimensions to assist panel builders.

Minimised flange option available (see page 258).

**IP67
WATERTIGHT
380 - 415V
50 - 60 Hz**

Plugs

Connectors

Socket Outlets
ANGLED

STRAIGHT

SURFACE

SURFACE – LOOP IN PANEL MOUNTING

Amps Pin.
Config-
uration Earth
Hour
Pos



16	3P+E	6
16	3P+N+E	6
32	3P+E	6
32	3P+N+E	6
63	3P+E	6
63	3P+N+E	6
125	3P+E	6
125	3P+N+E	6

K9025RED
K9026RED
K9055RED
K9056RED
K9282RED
K9292RED
K9092RED
K9097RED

K9125RED
K9126RED
K9157RED
K9158RED
K9842RED
K9852RED
K9182RED
K9187RED

K9763RED
K9764RED
K9765RED
K9766RED
K9858RED
K9859RED

K13025RED
K13026RED
K13055RED
K13056RED

K9191RED
K9192RED

K9812RED
K9822RED
K9481RED
K9482RED

Suitable for flexible cable only. 63A and 125A have external clamp.

Suitable for flexible cable only. 63A and 125A have external clamp.

2 x 29/37mm knockouts (top), 1 x Ø29 and 1 x Ø23 knockout (bottom). Will accept FL13 flanges top and bottom.

16/32A Fitted with terminals for Loop In. Suitable for top entry 2 x Ø25.

125A Fitted with terminals for Loop In. 2 x 23/47mm knockouts top and bottom for looping 2 x 10mm².

63/125A plugs and inlets include pilot pins.
63A connectors and sockets with pilot sleeves are available to special order.
125A Switchsocket interlocked outlets include pilot sleeves are available to special order.
All products are available in minimum order quantity of one.
Photographs feature the most representative products.
Design changes may occur (over different current ratings) from one product to another.