



## wiring devices | decorative

|                         | DUAL VOLTAGE<br>115/230V<br>OUTPUT<br>(120/130V<br>50/60HZ INPUT)<br>NON UK<br>FLUSH | Flex Outlets<br>(NON UK) | Plateswitches<br>10 AMP<br>FLUSH | 2 GANG SP<br>TWO-WAY<br>FLUSH | 3 gang sp<br>Two-way<br>FLUSH |
|-------------------------|--------------------------------------------------------------------------------------|--------------------------|----------------------------------|-------------------------------|-------------------------------|
| FINISHES                |                                                                                      | •••                      | •                                | •                             |                               |
| BRUSHED STAINLESS STEEL |                                                                                      | K2240BSS                 | K4671BSS                         | K4672BSS                      | K4673BSS                      |
| BRUSHED CHROME          | K707BRC                                                                              | K2240BRC 5               | K4671BRC                         | K4672BRC                      | K4673BRC                      |
| SATIN GOLD              |                                                                                      | K2240SAG                 | K4671SAG                         | K4672SAG                      | K4673SAG                      |
| POLISHED CHROME         |                                                                                      |                          | K4671PCR 5                       | K4672PCR 5                    | K4673PCR                      |

## MOUNTING BOXES: FLUSH: 878ZIC

This design incorporates a double wound isolating transformer rated 20VA at 230 or 115 volts and meets BS EN 61558-2-5:1998 making it safe for use in bathrooms.

Insertion of a shaver/ DIMENSIONS: 86 x 86mm Maximum 14.5mm toothbrush plug automatically FIXING CENTRES: 60.3mm switches on by energising the primary side of the isolating transformer – removal automatically switches DIMENSIONS: BS EN 60669-1: 1999 1 gang: 86 x 86mm If an intermediate switch is required, a modular (Grid Plus) version is available. Order K3431 grid plate, K3701 grid frame FIXING CENTRES: 1 gang: 60.3mm off. The transformer is and K4893WHI 20A intermediate switch. protected against overload BS 5733: 2010 by an automatic solid state overload device with automatic resetting. DIMENSIONS: 146 x 86mm FIXING CENTRES: 120.6mm BS EN 61558-2-5: 1998

MOUNTING BOXES: FLUSH: 866ZIC SURFACE (BRC) WITH KNOCKOUTS: K899ALM

WITHOUT KNOCKOUTS: K829ALM

Cable diameter: Minimum 4mm

## MOUNTING BOXES:

FLUSH: 3995ZIC

SURFACE (BRC) : WITH KNOCKOUTS: K899ALM WITHOUT KNOCKOUTS: K829ALM

These switches do not have to be derated when used with fluorescent or inductive loads.

Switches can be wired as either one-way or two-way.