

LJU6C Datacom
ModulesRJ45
CAT 6
SCREENED
ONE MODULERJ45
CAT 5E
ONE MODULELJU6C Datacom
BlanksLJU6C
ONE MODULE
(22 X 37MM)

TV/Satellite

TV/FM
SINGLE
NON-ISOLATED

FINISHES

BRUSHED STAINLESS STEEL

LACQUERED BRUSHED STEEL

SILVER ANODIZED ALUMINIUM

BRUSHED CHROME

POLISHED CHROME

SATIN GOLD

PORCELAIN WHITE

LUSTROUS BLACK

LUSTROUS BLACK

POLISHED BRASS

TEXTURED IRON

DESERT BRONZE

ANTIQUE BRASS

TEXTURED COPPER

K5746SWHI

5

K5745WHI

5

K170WHI

10

K14320BSS*

1

K14320LBS*

1

K14320SAA*

1

K14320BRC*

1

K14320POC*

1

K14320SAG*

1

K14320WHIW

1

K14320LIVW

1

K14320LBKB

1

K14320PBR*

1

K14320TIRB

1

K14320DBZB

1

K14320ABSB

1

K14320TCOB

1

LEAD TIMES: Please
contact our Customer
Services Department on:
01268 563 404

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterix, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

Cat 6 performance.

Suitable for both 568A and
568B wiring schemes.

MOUNTING BOXES:
Minimum Box Depth 35mm

ISO/IEC 11801
EN 50173
TIA 568
EN 41003

Enhanced Cat 5 performance.

Suitable for both 568A and
568B wiring schemes.

MOUNTING BOXES:
Minimum box depth 25mm

ISO/IEC 11801
EN 50173
TIA 568
EN 41003

MOUNTING BOXES:

Minimum box depth 16mm

BS 5733: 2010 where
appropriate

MOUNTING BOXES:

FLUSH: 861ZIC

SURFACE K2140WHI

Single outlet for
connection to a single TV
or FM co-axial aerial lead.

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS 3041: 1977
IEC169-2: 1965
BS 5733: 2010 where
applicable