

technical hotline +44 (0)1268 563720

modular | wiring devices

20 AMP SP
TWO-WAY
RED ROCKER

20 AMP SP
TWO-WAY
SWITCH WITH
INTEGRAL NEON
LOCATOR

20 AMP SP
TWO-WAY
AND CENTRE OFF
LATCHING

20 AMP SP
RED ROCKER
TWO-WAY
AND CENTRE OFF
LATCHING

20 AMP
INTERMEDIATE

20 AMP
INTERMEDIATE
RED ROCKER


K4892RED

10

K4892LWHI

10

K4899WHI

10

K4899RED

10

K4893WHI

10

K4893RED

10

K4892REDB

10

K4892LBLK

1

K4899BLK

10

K4893BLK

10

K4893REDB

10

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 1999