

technical hotline +44 (0)1268 563720

white | wiring devices

Euro Datacom Modules

RJ11/12



K5887WHI



K5887BLK

K5887WHI
K5887BLK
RJ11/12
ONE MODULE 25 X 50MM

Suitable for both RJ11 and RJ12 jacks
RJ11; 4 wire
RJ12; 6 wire
MOUNTING BOXES:
Minimum box depth 25mm
FCC68
EN 41003

RJ45 CAT 6



K5846WHI



K5846sBLK



K5864WHI

K5846WHI
K5846BLK
RJ45 CAT 6
ONE MODULE 25 X 50MM
K5846sWHI
K5846sBLK
RJ45 CAT 6 SCREENED
ONE MODULE 25 X 50MM
K5864WHI
RJ45 CAT 6 ANGLED
ONE MODULE 25 X 50MM

Cat 6 performance.
Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES:
Minimum Box Depth 35mm
ISO/IEC 11801
EN 50173
TIA 568
EN 41003

RJ45 CAT 5E



K5844WHI



K5845WHI



K5845BLK

K5844WHI
RJ45 CAT 5E ANGLED
ONE MODULE 25 X 50MM
K5845WHI
K5845BLK
RJ45 CAT 5E
ONE MODULE 25 X 50MM

Enhanced Cat 5 performance.
Suitable for both 568A and 568B wiring schemes.
Supplied with cable tie and cable anchors to secure wires in the connectors.
MOUNTING BOXES:
Minimum box depth 25mm standard
ISO/IEC 11801
EN 50173
TIA 568
EN 41003

TELEPHONE



K5820WHI



K5821WHI



K5821BLK

K5820WHI
K5820BLK
TELEPHONE MASTER
ONE MODULE 25 X 50MM
K5821WHI
K5821BLK
TELEPHONE SECONDARY
ONE MODULE 25 X 50MM

MOUNTING BOXES:
Minimum depth 25mm
BS 6312 Pt 2

BNC



K5801WHI

K5801WHI
BNC 50Ω
ONE MODULE 25 X 50MM

50 Ohm crimp connector suitable for use with RG58, URM43, URM76 and Belden 9907 type co-axial cables.
MOUNTING BOXES:
Minimum box depth 25mm

Mains operated products and extra low voltage modules must not be installed within the same frontplate.
Refer to BS 7671: 2008 for details.