

**IP44  
SPLASHPROOF  
200 - 250V  
50 - 60 Hz**

### Plugs



### Connectors



### Socket Outlets ANGLED

#### SURFACE



#### SURFACE-LOOP IN



### STRAIGHT PANEL MOUNTING



Amps Pin. Config-uration Earth Hour Pos

Amps	Pin. Config-uration	Earth Hour Pos	Plugs	Connectors	Socket Outlets ANGLED SURFACE	Socket Outlets ANGLED SURFACE-LOOP IN	Socket Outlets STRAIGHT PANEL MOUNTING
16	2P+E	6	<b>K9001BLU</b>	<b>K9101BLU</b>	<b>K9201BLU</b>	<b>K13201BLU</b>	<b>K9401BLU</b>
16	3P+E	9	<b>K9006BLU</b>	<b>K9106BLU</b>	<b>K9206BLU</b>		<b>K9406BLU</b>
16	3P+N+E	9	<b>K9014BLU</b>	<b>K9114BLU</b>	<b>K9214BLU</b>		<b>K9414BLU</b>
32	2P+E	6	<b>K9033BLU</b>	<b>K9133BLU</b>	<b>K9233BLU</b>	<b>K13233BLU</b>	<b>K9433BLU</b>
32	3P+E	9	<b>K9036BLU</b>	<b>K9136BLU</b>	<b>K9236BLU</b>		
32	3P+N+E	9	<b>K9044BLU</b>	<b>K9143BLU</b>	<b>K9240BLU</b>		<b>K9444BLU</b>
63	2P+E	6	<b>K9063BLU</b>	<b>K9172BLU</b>	<b>K9274BLU</b>		<b>K9472BLU</b>
63	3P+E	9	<b>K9065BLU</b>	<b>K9164BLU</b>	<b>K9264BLU</b>		

**16A/32A** Fitted with cable entry gland.

**63A** Fitted with cable entry gland.

Thread size M48.

BS EN 60309

**16A/32A** Fitted with cable entry gland.

**63A** Fitted with cable entry gland.

Thread size M48.

BS EN 60309

**16A** Top conduit (M20) or rear cable entry, complete with blanking plug.

**32A** Top conduit (M25) or rear cable entry, complete with blanking plug.

**63A** Top conduit (M32) or rear cable entry, complete with blanking plug.

BS EN 60309

Suitable for top entry 2 x Ø25.

Fitted with terminals for Loop In 2 x 10mm<sup>2</sup>.

BS EN 60309

**16/32A** All flanges have the same fixing centres and outside dimensions to assist panel builders.

Minimised flange option available (see page 258).

BS EN 60309

**IP67  
WATERTIGHT  
200 - 250V  
50 - 60 Hz**

### Plugs



### Connectors



### Socket Outlets ANGLED

#### SURFACE



#### SURFACE - LOOP IN



### STRAIGHT

#### PANEL MOUNTING



Amps Pin. Config-uration Earth Hour Pos

Amps	Pin. Config-uration	Earth Hour Pos	Plugs	Connectors	Socket Outlets ANGLED SURFACE	Socket Outlets ANGLED SURFACE-LOOP IN	Socket Outlets STRAIGHT PANEL MOUNTING
16	2P+E	6	<b>K9024BLU</b>	<b>K9124BLU</b>	<b>K9194BLU</b>	<b>K13024BLU</b>	
32	2P+E	6	<b>K9054BLU</b>	<b>K9156BLU</b>	<b>K9762BLU</b>	<b>K13054BLU</b>	
63	2P+E	6	<b>K9298BLU</b>	<b>K9856BLU</b>	<b>K9857BLU</b>		<b>K9828BLU</b>
63	3P+E	9					
125	2P+E	6	<b>K9099BLU</b>	<b>K9189BLU</b>		<b>K9190BLU</b>	<b>K9483BLU</b>

Suitable for flexible cable only 63A and 125A. With external clamp.

BS EN 60309

Suitable for flexible cable only 63A and 125A. With external clamp.

BS EN 60309

Suitable for top entry 2 x Ø25 or bottom entry 2 x Ø20.

Will accept FL13 flange at top.

BS EN 60309

**16/32A** Suitable for top entry 2 x Ø25

**125A** 2 x 23/47mm knockouts top and bottom.

BS EN 60309

**IP44  
SPLASHPROOF  
200 - 250V  
50 - 60 Hz  
16 Amps  
2P + E**

### Socket Outlets ANGLED TWIN



**SURFACE**  
Prewired Unwired

**K13144BLU K13044BLU**

Suitable for top entry 2 x Ø25 / 2 x Ø38

Bottom entry 3 x 47.5mm

BS EN 60309

63/125A plugs and inlets include pilot pins.

63A connectors and sockets with pilot sleeves are available to special order.

125A Switchsocket interlocked outlets with pilot sleeves are available to special order.

All products are available in minimum order quantity of one except K9001 and K9101 which have minimum order quantities of 10.

Photographs feature the most representative products.

Design changes may occur (over different current ratings) from one product to another.