

technical hotline +44 (0)1268 563720

white | wiring devices

Standard Dimmer Switches

230V a.c. 50Hz
TUNGSTEN FILAMENT
FLUSH



K1511WHI



K1531WHI



K1532WHI



K1533WHI

Dimmer Switches

230V a.c. 50Hz
COMPACT
FLUORESCENT
FLUSH



K1525WHI

Dimmer Switches (NON UK)

200-250V a.c.
50 or 60Hz
FLUSH



K1541WHI



K1561WHI



K1631WHI




K1661WHI

Blank Plates

FLUSH



K3825WHI



K3827WHI



K3828WHI



K5033WHI

Flex Outlet Frontplate

FLUSH



K1090WHI

K1511WHI

 1 GANG SINGLE
ONE WAY 65-450W

K1531WHI

 1 GANG SINGLE
ONE WAY 40-250W

K1532WHI

 1 GANG DOUBLE
ONE WAY 2 x 40-250W

K1533WHI

 1 GANG DOUBLE
TWO WAY 2 x 40-250W

K1534WHI

 1 GANG SINGLE
TWO WAY 40-250W

K1535WHI

 1 GANG SINGLE
TWO WAY 65-450W

MOUNTING BOXES:

FLUSH: 861ZIC-25mm deep. With pattress: 3995ZIC-16mm deep min
SURFACE: K2140WHI-30mm deep. With pattress: K2160WHI-16mm deep min
Only suitable for tungsten filament lamps.

NOT suitable for fluorescent lamps or low voltage lighting.

DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm
Conforms to BS EN 60669-2-1 and BS EN 55015

1

1

1

1

1

1

K1525WHI

 1 GANG SINGLE
TWO WAY 11-300W
240VA FOR COMPACT
FLUORESCENT LAMPS ONLY

MOUNTING BOXES:

FLUSH:
With pattress: 16mm deep min 3995ZIC
Without pattress: 25mm deep min 861ZIC

SURFACE: K2160WHI/K2140WHI
Dimmers comply with BS EN 55015 (CISPR15) for RFI suppression.

Micro controller based circuitry to provide electronic starting and overload protection for dimmable compact fluorescent lamps. This product is designed to start at full brightness regardless of dimmer setting automatically adjusting to the desired level after a short period

Max number of lamps (4)
DIMENSIONS: 86 x 86MM
FIXING CENTRES: 60.3MM
Conforms to BS EN 60669-2-1, BS EN 55015

1

K1541WHI

 1 GANG SINGLE
ONE WAY
75-500W 50Hz

K1561WHI

 1 GANG SINGLE
TWO WAY
100-1000W 50Hz

K1631WHI

 1 GANG SINGLE
ONE WAY
40-250W 60Hz

K1641WHI

 1 GANG SINGLE
ONE WAY
75-500W 60Hz

K1661WHI

 1 GANG SINGLE
TWO WAY
100-1000W 60Hz

K1539WHI

 FAN CONTROLLER
1 GANG SINGLE ONE WAY
300 VA 50Hz

MOUNTING BOXES:

FLUSH: 861ZIC-25mm deep min
SURFACE: K2140WHI-30mm deep

DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm

1

1

1

1

1

1

1

K3825WHI

 1 GANG MOULDED
ARCHITRAVE

K3827WHI

1 GANG MOULDED

K3828WHI

2 GANG MOULDED

K5033WHI

METAL

K3825WHI

For use with 3921ZIC and K2151WHI MOUNTING BOXES.

K5033WHI

For use with 5120ALM deep metal box.

DIMENSIONS:
K3825WHI: 86 x 31mm
K3827WHI: 86 x 86mm
K3828WHI: 86 x 146mm
K5033WHI: 178 x 165mm

FIXING CENTRES:
K3825WHI: 60.3mm
K3827WHI: 60.3mm
K3828WHI: 120.6mm
K5033WHI: 133mm

BS 5733: 2010

10

10

10

1

K1090WHI

 FLEX OUTLET FRONTPLATE.
UNFUSED
20 AMP RATING

Complete with three pairs of terminals, each suitable for 2 x 2.5mm² conductors and a 1.5mm² flexible cord. A cord-grip is also fitted.

Frontplate thickness is 12.5mm. Hole diameter is 11mm.

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS 5733: 2010

10