

Switchsocket  
Outlets

MINI LOGIC  
13 AMP  
SURFACE

Socket Outlets  
For Circular  
Conduit Boxes

ROUND PIN

Switchsocket  
Outlets

13 AMP  
PANEL MOUNTING



## Socket Outlets

13 AMP  
PANEL MOUNTING



## DP Switch

TWIN  
25 AMP  
MOULDED  
FLUSH



**2959WHI**  
1 GANG SP

10

**2949WHI**  
2 GANG SP

5

**312WHI\***  
1 GANG  
2A  
UNSHUTTERED

10

**315WHI**  
1 GANG  
5A  
SHUTTERED

10

**2531WHI**  
1 GANG SP  
SWITCHSOCKET

5

**2532WHI**  
2 GANG SP  
SWITCHSOCKET

5

**734WHI**  
1 GANG  
CRUCIFORM SOCKET

10

**735WHI**  
1 GANG  
CIRCULAR SOCKET

10

**1232D1**  
1 GANG  
NON STANDARD

10

**5257WHI**  
TWIN DP SWITCH

5

**5243BRO**  
MOULDED PHASE BARRIER  
FOR SURFACE APPLICATIONS

5

**5246BRO**  
MOULDED PHASE BARRIER  
FOR FLUSH APPLICATIONS

5

These products are supplied with a mounting box.

Mounting boxes have knockouts for cables.

DIMENSIONS:  
1 gang: 74 x 64 x 46mm  
2 gang: 133 x 64 x 46mm  
BS 1363 Pt.2:1995

These products are designed for use with circular conduit boxes to BS 4568: Pt.2:1970. See page 368. \*The IEE Wiring Regulations does not recommend the use of unshuttered sockets in household situations

DIAMETER:  
68mm  
FIXING CENTRES:  
50.8mm  
BS 546:1950

Supplied with M3.5 threaded eyelets and fixing screws.  
These products have side entry terminals.  
BS 1363 Pt.2:1995

Supplied with M3.5 threaded eyelets and fixing screws.

**734** and **735** have side entry terminals.

They are also available with rear entry terminals. Use suffix D5WHI when ordering.

**1232D1** has rear entry terminals and is provided with facilities for 'clean earth' connection and are suitable for non-standard plugs with 'T' shaped earth pin.

**734, 735**  
BS 1363 Pt.2:1995

**1232D1**  
BS 1363 Pt.2:1995 where relevant.

MOUNTING BOXES  
FLUSH: 886ZIC

SURFACE: 2182WHI

Suitable for installation in boxes to a minimum depth of 35mm. Complete with earth terminals and thermostat looping terminal

DIMENSIONS: 86 x 146mm  
FIXING CENTRES: 120.6mm

DIAMETER OF FLEX OUTLETS:  
11mm for 'FAN'  
13mm for 'HEATER'

BS EN 60669-1: 1999

**MOULDED PHASE BARRIERS**  
Self-adhesive labels are supplied for application to interior and exterior of switch to indicate when voltage exceeds 250 volts.