

technical hotline +44 (0)1268 563720

white | wiring devices

Simple Fit Sensors

Standard PIRs

Superior PIRs

BattenFit Sensors

IP65



K5015



K4010



K4015



K4041 / K4042
K4043 / K4044



K4046 / K4047
K4048 / K4049



K5016



K4011



K4017

K5015 1
SIMPLE FIT PHOTOCELL WITH PIR
FLUSH MOUNTED
6A

K5016 1
SIMPLE FIT PHOTOCELL WITH PIR
SURFACE MOUNTED
6A

K4010
SLIM FLUSH, 6A

K4011
SURFACE, 6A

K4015
SLIM FLUSH, 6A

K4016
SURFACE, 6A

K4017
DUAL CIRCUIT, FLUSH, 6A

K4018
DUAL CIRCUIT, SURFACE, 6A

K4019
SLIM FLUSH
9 X DSI BALLASTS

K4020
SURFACE
25 X DSI BALLASTS

K4041
BATTENFIT SENSOR
2A SWITCHING

K4042
BATTENFIT SENSOR
2A SWITCHING PCELL

K4043
BATTENFIT SENSOR
REGULATING PCELL DSI

K4044
BATTENFIT SENSOR
REGULATING PCELL DALI

K4046
BATTENFIT SENSOR
2A SWITCHING
IP65

K4047
BATTENFIT SENSOR
2A SWITCHING PCELL
IP65

K4048
BATTENFIT SENSOR
REGULATING PCELL DSI
IP65

K4049
BATTENFIT SENSOR
REGULATING PCELL DALI
IP65

DIMENSIONS:
Flush: 76 x 86mm
Surface: 86 x 86mm x 54.5mm

DIMENSIONS:
Slim: 65 x 115mm
Surface: 100 x 72mm

DIMENSIONS:
Slim: 65 x 115mm
Surface: 100 x 72mm

DIMENSIONS:
121 x 40 x 29mm

DIMENSIONS:
150 x 40 x 29mm