



Wall Mounting Accessories

AC, Modular chassis



Description: Used for easy mounting of DIN-rail components with a maximum height of 68mm. Distance between rows 125mm. If required, the standard enclosure door can be replaced with a glazed door. Usable depth between front cover and external door: 35mm. Adjustable depth position with AMG accessory. In stainless steel enclosure machining is required.

Material: DIN-rails PP0735 made of 1.20mm galvanized steel, vertical profiles 1.5mm mild steel, and front cover 1.5mm mild steel.

Finish: RAL 7035 structure powder coating.

Pack quantity: Slotted front panel, two vertical profiles, top and bottom blank panels, one DIN-rail per row, and mounting accessories.

For enclosure		N° of modules	N° of rows	Part No.
H	W			
300	250	16	2	AC03025R5
400	300	33	3	AC04030R5
500	400	48	3	AC05040R5
600	400	64	4	AC06040R5
	600	108	4	AC06060R5
700	500	110	5	AC07050R5
800	600	162	6	AC08060R5
1000	600	216	8	AC10060R5
	800	304	8	AC10080R5

ADSW, MultiMount door switch



Description: To activate any electrical device (Lighting, signalling, alarm, etc.). Cable entry M20. In stainless steel enclosure, machining is required.

Switch capacity: 6A / 230V.

Approvals: UL and CSA approved.

Pack quantity: 1 piece with mounting accessories.

Part No.
ADSW01

ADI, Inner doors



Description: For controls, meters, lamps, etc. Hinges can be mounted to allow left or right hand opening. Lock double-bit 3mm insert; 700mm high doors and above have 2 locks. Usable depth between inner and external door: 35mm. Adjustable depth position with AMG accessory. Workable area: H-55, W- 108. In stainless steel enclosure machining is required.

Material: Door 1.5mm mild steel, and vertical profiles 2mm mild steel.

Finish: RAL 7035 structure powder coating.

Pack quantity: Inner door, two vertical profiles and mounting accessories.

Enclosure dimension			N° of		Part No.
H	W	h	w	locks	
400	300	345	192	1	ADI04030R5
	400	345	292	1	ADI04040R5
	500	345	392	1	ADI04050R5
	600	345	492	1	ADI04060R5
500	300	445	192	1	ADI05030R5
	400	445	292	1	ADI05040R5
	500	445	392	1	ADI05050R5
600	400	545	292	1	ADI06040R5
	500	545	392	1	ADI06050R5
	600	545	492	1	ADI06060R5
	800	545	692	1	ADI06080R5
700	500	645	392	2	ADI07050R5
800	400	745	292	2	ADI08040R5
	600	745	492	2	ADI08060R5
	800	745	692	2	ADI08080R5
1000	600	945	492	2	ADI10060R5
	800	945	692	2	ADI10080R5
1200	600	1145	492	2	ADI12060R5
	800	1145	692	2	ADI12080R5

ADIS, Inner doors



Description: For controls, meters, lamps, etc. Hinges can be mounted to allow left or right hand opening (Machining is required). Double-bit 3mm lock, 500mm high doors and above have 2 locks. Usable depth between inner and external door: 35mm, adjustable depth position with AMG accessory. Workable area: H-55, W-108.19" version also available.

Material: Door 1.5mm AISI 304 stainless steel.

Finish: 240s pre-grained stainless steel (average 0.5 micron)

Pack quantity: 1 piece with mounting accessories.

Enclosure dimension		Part No.
H	W	
400	300	ADIS04030
500	500	ADIS05050
600	400	ADIS06040
	600	ADIS06060
800	600	ADIS08060
1000	800	ADIS10080
1200	800	ADIS12080

To order 19" version, please add I19 to the catalogue no, e.g. ADIS04030I19