Inspiration starts here PRODUCT SELECTOR

BS EN 60669-1:1999

BS EN 60669-1:1999

BS EN 60669-1:1999

SWITCH MODULES 20 AMP						
RED ROCKER 2 WAY AND CENTRE OFF SP 20 AMP	INTERMEDIATE 20 AMP	INTERMEDIATE RED ROCKER 20 AMP	1 WAY DP 20 AMP	1 WAY NEON DP 20 AMP	1 WAY WITH WINDOW DP 20 AMP	1 WAY RED ROCKER DP 20 AMP
FUNCTIONAL MODU	JLES					
K4899RED	K4893WHI	K4893RED	K4896WHI	K4896NWHI	K4896WWHI	K4896RED
K4899REDB	K4893BLK	K4893REDB	K4896BLK	K4896NBLK	K4896WBLK	K4896REDB
These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT have to be derated when used with fluorescent or inductive loads.	These switches do NOT haveto be derated when used withfluorescent or inductive loads.

BS EN 60669-1:1999

BS EN 60669-1:1999

BS EN 60669-1:1999

BS EN 60669-1:1999