Inspiration starts here

PRODUCT SELECTOR

ACCESSORY MODULES											
SINGLE TV CO-AXIAL OUTLET NON-ISOLATED	SINGLE TV CO-AXIAL OUTLET ISOLATED	200-250V A.C. BUZZER UNIT	21-36V A.C. BUZZER UNIT	16A CORD OUTLET	13A FUSE UNIT	13A FUSE UNIT WITH TAMPERPROOF SCREW					















FUNCTIONAL MODULES											
White	K4520WHI	K4521WHI	K4000WHI	K4001WHI	K4886WHI	K4890WHI	K4890KOWHI				
Black	K4520BLK	K4521BLK			K4886BLK	K4890BLK	K4890KOBLK				

For direct connection to TV or FM aerial co-axial downlead. NOT to be used in same enclosure as mains exceeding 50V.
BS 3041:1977 IEC 169-2:1965 BS 5733:2010 where applicable.

For direct connection to TV or FM aerial co-axial downlead. NOT to be used in same enclosure as mains exceeding 50V. BS 3041:1977 IEC 169-2:1965

BS 5733:2010 where applicable.

SOUND OUTPUT SOUND OUTPUT LEVEL LEVEL Av 61 db @ 15 feet. BS 5733:2010

Av 61 db @ 15 feet. BS 5733:2010

Complete with 3 pairs of terminals. The supply terminals are suitable for up to 2 x 2.5mm² or 1 x 4mm² solid conductors. The load terminals are suitable for one 1.5mm² flexible cord. A cord grip is also fitted. BS 5733:2010

Fuse carrier fitted with 13A cartridge fuse link to BS 1362. BS 5733:2010

Fuse carrier fitted with 13A cartridge fuse link to BS 1362. BS 5733:2010 Key (3405ZIC) is supplied.