

Deta Connect

Slave Dimmers

- Slave Dimmers are used to create 2-way control and are wired to master dimmers
- Up to 6 slaves per master dimmer to create 2-way and intermediate dimming
- 3 Core wiring between master and slave dimmers
- Requires 35mm back box
- In compliance with BS EN 60669-2-1
- 2-year guarantee

Slave Dimmers

Chrome/Satin Chrome/White

9511CHW 1 gang

9511SCW

9511WHW

9512CHW 2 gang

9512SCW

9512WHW



9511CHW



9511SCW



9511WHW



9512CHW



9512SCW



9512WHW

CONNECT

Master / Slave Dimmers

- 1st gang is a master dimmer, the 2nd gang is a slave dimmer, ideal for hall way / landing switching
- Slave must be used with a master dimmer
- Up to 6 slaves per master dimmer to create 2-way and intermediate dimming
- Requires 35mm back box
- In compliance with BS EN 60669-2-1
- 2-year guarantee

Master / Slave Dimmers

Chrome/Satin Chrome/White

9515CHW

9515SCW

9515WHW



9515CHW



9515SCW



9515WHW

Back Boxes

minimum recommended depth

	flush 35mm	dry lining 35mm
1g	DB164	DB2547

DETA
Connect
...to a smart home

Telesales Hotline 01582 544 544