TFB4 Cavity Floor Boxes

TFB4/64 Clearance 20mm knockouts only on TFB3/64, as this Slim flooxbox is designed for installation were space is limited



TFB4/76







Specifications TFB4 Range

- Floor box manufactured from galvanised steel
- 20 & 25mm knockouts to accept flexible conduit
- Frame & lid moulded from high impact polycarbonate (RAL7031)
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Clean Earth Sockets available

- Compact design 303 x 221mm floor cut-out
- Clamp fixing for fast installation
- Large range of accessory plates, colour equivalent: RAL7035
- Suitable for carpeted floors only with standard Frame & Lid
- ABS Plastic Frame & Lid Load Test 550 KG
- Steel Frame & Lid Load Test 740 KG

Note: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice.

TFB4 Cavity Floor Boxes



Model	Description	Depth	Plug Clearance	Frame & Lid	Plate Size	Floor Cutout
TFB4/64	4 Compt Cavity Floorbox	64mm	24mm	313 x 230mm	185 x 68mm	303 x 221mm
TFB4/76	4 Compt Cavity Floorbox	76mm	25mm	313 x 230mm	185 x 68mm	303 x 221mm
TFB4/80	4 Compt Cavity Floorbox	80mm	30mm	313 x 230mm	185 x 68mm	303 x 221mm
TFB4/86	4 Compt Cavity Floorbox	86mm	36mm	313 x 230mm	185 x 68mm	303 x 221mm
TFB4/120	4 Compt Cavity Floorbox	120mm	70mm	313 x 230mm	185 x 68mm	303 x 221mm

TFB4 RCD Protected Cavity Floor Box



Model	Description	Depth	Clearance	Frame & Lid	Plates Size	Floor Cutout
TFB4/RCD	4 Compt RCD Cavity Floorbox	90mm	35mm	313 x 230mm	185 x 68mm	303 x 221mm

Note: Data, voice and audio visual modules are sold seperately, see pages 48-49 for details.