

General Information				
Dimmable/Non-Dimmable	Non-Dimmable		Dimmable	
LED Colour Temperatures Available	2700K (Warm)	4000K (Cool)	2700K (Warm)	4000K (Cool)
Finish Colours Available	White, Chrome & Satin Chrome			
Material Composition	Steel, Aluminium, ABS, Nylon & Polycarbonate			
Cut-Out	65-75mm			
Ceiling Thickness	5-40mm			
Ceiling Void depth	50mm+			
Dimensions	Height: 55mm, Diameter: 87mm (front)			
Warranty	Registered: 7 Years Domestic. Unregistered 1 Year			
Weight	0.266Kg		0.266Kg	
Light Output Information				
Beam Angle	35°		35°	
CRI	80		80	
LED Lifetime (L70)	30,000 hours		30,000 hours	
Luminous Flux	WW: 400lm CW: 420lm (lumens)		WW: 400lm CW: 420lm (lumens)	
Luminous Efficacy	60lm/W		55lm/W	
Power Factor	0.9		0.85	
Driver Information				
Connection	Integrated Flow® Connector			
Input	200-240V / 7W max (non-dimmable) 7.5W max (dimmable)			
Output	Driver Output Current: 150mA – Output Voltage: 36V			
Critical Temperature	70°C			
Part L1 Compliancy (as of 2012)	Yes		Yes	
Part L2 Compliancy (as of 2012)	Yes		Yes	
Regulation Ratings				
Fire Rating	30, 60 & 90 minute			
Acoustic Rating	0dB (zero impact on sound insulation)			
Air Flow	BS 5250: 2002 compliant			
Other Information				
Halogen Content	Completely Halogen-free			



Scolmore[®]
GROUP
Scolmore Park, Landsberg,
Lichfield Road Industrial Estate,
Tamworth, Staffordshire
B79 7XB United Kingdom

T: +44 (0)1827 63454
F: +44 (0)1827 63362
E: sales@scolmore.com

www.scolmore.com

click[®] Litehouse

18 Corrig Road
Sandyford
Dublin 18
Ireland

T: +353 (1) 2811 122
F: +353 (1) 2811 224
E: sales@clicklitehouse.ie

www.clicklitehouse.ie

Features

- Flow Connector
- FlameGuard; Proven Fire-Rated technology
- Choice of Fixed and Adjustable Bezels included
- Compact, Integrated Driver
- 60 Lm/W Luminous Efficacy (55Lm/W for dimmable)
- 35° Beam Angle
- 30,000 hour LED lifetime
- 7 Years guaranteed (domestic installations only)



The Inceptor Micro downlights are covered by a 7 year warranty. Only valid once registered online by the end user at www.scolmore.com.

Benefits


- Flow Connector for quick and convenient wiring
- FlameGuard technology for maintained protection in 30, 60 and 90 minute Fire-Rated ceilings
- Compact size; product will fit into a 50mm void depth
- Part L compliant
- 35° Beam angle with a neat and even spread of light
- Option of fixed or adjustable bezel supplied as standard

Wholesaler:

- No need to stock two types of product; one product provides both adjustable and fixed options.

End-User:

- Flexibility to switch between bezels if requirements change




Pre-wired *flow* Connector

Pre-wired *flow* Connector - For quick connection and removal. Use with the Click Flow range of connectors, pre-wired cables and Hub (CT300).



Low Profile

Fits Into
50mm
void depth



Compact Driver

The Inceptor Micro's high powered compact driver, is as small as a fire rated ceiling will accommodate. Another small detail, that makes a big difference when space is limited.

Intumescent Strip


Our trademark blue strip of intumescent adds an extra barrier of protection against fire, by expanding to fill the gap between plasterboard and light fitting.

SMD LED Technology

SMD LED's require lower current and create less heat than standard LEDs, perfect when space is at a premium.

ONE FITTING, TWO OPTIONS

Each Inceptor Micro comes with both fixed and adjustable bezels.



inceptor
micro

Inceptor Micro Downlight, Fire & Acoustic Rated Pre-Wired with Driver and Flow Connector (non-dimmable)

LED4300WH7W	7W Integrated LED - Warm White	White Bezel
LED4300CH7W	7W Integrated LED - Warm White	Chrome Bezel
LED4300SC7W	7W Integrated LED - Warm White	Satin Chrome Bezel
LED4300WH7C	7W Integrated LED - Cool White	White Bezel
LED4300CH7C	7W Integrated LED - Cool White	Chrome Bezel
LED4300SC7C	7W Integrated LED - Cool White	Satin Chrome Bezel

Inceptor Micro Downlight, Fire & Acoustic Rated Pre-Wired with Dimmable Driver and Flow Connector

LED4300WH7WD	7.5W Integrated Dimmable LED - Warm White	White Bezel
LED4300CH7WD	7.5W Integrated Dimmable LED - Warm White	Chrome Bezel
LED4300SC7WD	7.5W Integrated Dimmable LED - Warm White	Satin Chrome Bezel
LED4300WH7CD	7.5W Integrated Dimmable LED - Cool White	White Bezel
LED4300CH7CD	7.5W Integrated Dimmable LED - Cool White	Chrome Bezel
LED4300SC7CD	7.5W Integrated Dimmable LED - Cool White	Satin Chrome Bezel