

## Locks for NSYCRN

Characteristics	Key Operated Product Ref	Reference
Full Key Operated Lock with Key 405		NSYCL405CRN
6 mm Square Key Lock	LC-7	NSYTC6CRN
7 mm Square Key Lock	LC-7	NSYTC7CRN
8 mm Square Key Lock	LC-8	NSYTC8CRN
6 mm Triangular Key Lock	LT-6,5	NSYTT6CRN
7 mm Triangular Key Lock	LT-8	NSYTT7CRN
8 mm Triangular Key Lock	LT-8	NSYTT8CRN
Stainless Steel Padlock Bracket		NSYKPLM
Padlock Transformation		NSYCBCCRN



\* Various lock configurations are available for the NSYCRNG enclosure. Please ask our customer service department for further details.

### Spare Keys

Characteristics	Reference
Manual handle with key	405 - NSYCL40SCRN
Wing	NSYLDBS

### Canopies

Metal canopies, protected internally and externally with textured light grey polyester epoxy resin, to RAL7035.

Reference	Width	Depth
NSYTJ2015	200	150
NSYTJ2515	250	150
NSYTJ2520	250	200
NSYTJ3015	300	150
NSYTJ3020	300	200
NSYTJ4015	400	150
NSYTJ4020	400	200
NSYTJ4025	400	250
NSYTJ5015	500	150
NSYTJ5020	500	200
NSYTJ5025	500	250
NSYTJ6020	600	200
NSYTJ6025	600	250
NSYTJ6040	600	400
NSYTJ8020	800	200
NSYTJ8025	800	250
NSYTJ8030	800	300
NSYTJ8040	800	400
NSYTJ10030	1000	300
NSYTJ10040	1000	400

### Internal Door

Set of internal doors designed to attach directly to the enclosure or to the adjustable SDCR supports. Enter positioning of the mounting plate by making it depth adjustable. Finished in textured polyester epoxy paint, colour RAL7035.

Reference	Height	Width
NSYPIN43	400	300
NSYPIN54	500	400
NSYPIN64	600	400
NSYPIN75	700	500
NSYPIN86	800	600
NSYPIN106	1000	600
NSYPIN108	1000	800
NSYPIN128	1200	800

