

In 0.5 to 63A
Un : 230V-400V

Will accept accessories
see page 4.5

Description

These MCBs allow you to ensure

- Protection of circuits against short circuits
- Protection of circuits against overload current
- Control
- Isolation

Isolation

The state of isolation is clearly indicated by the "OFF" mechanical position on the toggle with the green colour.

Connection capacity

- 25mm² flexible conductor
- 35mm² rigid conductor


Complies with:

- BS EN 60898 (10kA)
- BS EN 60947-2 (15kA)

Triple Pole MCBs



NCN316A




Rating	Width (52.5mm)	Cat ref. "B" Curve	Cat ref. "C" Curve	Cat ref. "D" Curve
0.5A	3 Mod	-	NCN300A	NDN300A
1A	3 Mod	-	NCN301A	NDN301A
2A	3 Mod	-	NCN302A	NDN302A
3A	3 Mod	-	NCN303A	NDN303A
4A	3 Mod	-	NCN304A	NDN304A
6A	3 Mod	NBN306A	NCN306A	NDN306A
10A	3 Mod	NBN310A	NCN310A	NDN310A
16A	3 Mod	NBN316A	NCN316A	NDN316A
20A	3 Mod	NBN320A	NCN320A	NDN320A
25A	3 Mod	NBN325A	NCN325A	NDN325A
32A	3 Mod	NBN332A	NCN332A	NDN332A
40A	3 Mod	NBN340A	NCN340A	NDN340A
50A	3 Mod	NBN350A	NCN350A	NDN350A
63A	3 Mod	NBN363A	NCN363A	NDN363A

Four Pole MCBs



NCN416A



Rating	Width (70mm)	Cat ref. "B" Curve	Cat ref. "C" Curve	Cat ref. "D" Curve
0.5A	4 Mod	-	NCN400A	NDN400A
1A	4 Mod	-	NCN401A	NDN401A
2A	4 Mod	-	NCN402A	NDN402A
3A	4 Mod	-	NCN403A	NDN403A
4A	4 Mod	-	NCN404A	NDN404A
6A	4 Mod	NBN406A	NCN406A	NDN406A
10A	4 Mod	NBN410A	NCN410A	NDN410A
16A	4 Mod	NBN416A	NCN416A	NDN416A
20A	4 Mod	NBN420A	NCN420A	NDN420A
25A	4 Mod	NBN425A	NCN425A	NDN425A
32A	4 Mod	NBN432A	NCN432A	NDN432A
40A	4 Mod	NBN440A	NCN440A	NDN440A
50A	4 Mod	NBN450A	NCN450A	NDN450A
63A	4 Mod	NBN463A	NCN463A	NDN463A