

Simply child's play.

Getting started with the classic sensor.

Are you toying with the idea of fitting a motion detector to your building? The infrared controlled IS 140-2 motion detector gives you all the benefits of a modern detector. Needless to say, we always use the very latest technology for our bestsellers too. For instance, we have given the product in its current generation even more class: larger adjustment angle, even longer reach and even better detection performance. Treat your home to intelligent sensor technology.



- infrared sensor 140°
- max. 14 m
- IP54
- 1000w max.
- ideal 2 m
- 180° horizontal
90° vertical
- 2–2000 lux
- 8 sec. –35 min.
- energy saving
- 3 JAHRE GARANTIE
functional warranty



140°, max. 14 m

EAN IS 140-2 white	4007841 608910
EAN IS 140-2 black	4007841 608811
Type	motion detector
Dimensions (h x w x d)	70 x 86 x 95 mm
Power supply	230 - 240V/50Hz
Sensor type	passive infrared
Where to use	indoors and outdoors
Installation	wall
Max. output (resistive load, e.g. ordinary lamp)	1,000 W
Max. output (uncorrected, inductive, cos φ = 0.5, e.g. fluorescent lamps)	500 W
Max. output (electronic ballasts, capacitive, e.g. low-energy lamps)	6 each max., C ≤ 132 µF
Angle of coverage	140° with sneak-by guard
Capability of masking out individual segments	yes
Swivelling range	180°
Tilting range	90°
Reach	14 m max. (temperature-stabilised)
Response brightness	2 - 2,000 lx
Time setting	8 sec. - 35 min.
IP rating	IP54
Protection class	II
Optional accessory	Corner wall mount bracket 07 for mounting on external corners
EAN EWH 07 white	4007841 631765
EAN EWH 07 black	4007841 631864

For wall or corner mounting



white

black



UV-resistant plastic



Optional corner wall mount bracket 07

