

EMERGENCY

UNIVERSAL EMERGENCY BULKHEAD AVAILABLE IN STANDARD OR SELF-TEST



	Standard	Self Test Function
	R8MU-01	R8MUST-01
Total Luminous Flux L₁₀₀ (lm):	145	145
Emergency Luminous Flux L₁₀₀ (lm):	50	50
Illuminance @ 1m L₁₀₀ (lx):	23	23
Colour Temperature L₁₀₀ (K):	5000	5000
Colour Rendering Index L₁₀₀ (Ra):	80	80
Total Power(W):	8	8
Cut-out (mm):	280x135	280x135
Ambient Operating Temp (Deg)	0<T _a <40	0<T _a <40
Ingress Protection (IP):	20	20
Min Order/Box Quantity:	1/6	1/6
Cap Type:	G5	G5
Weight (Kg):	1.15kg	1.15kg
Guarantee (Yrs):	2	2
R8MULK-15	Dropped Legend Accessory	

It is a legal requirement to provide adequate emergency lighting and signage in our buildings. Traditionally it has been bulky and unattractive. Not so with these fittings. For all building types, recessed or surface mounted, wall or ceiling mounted, they combine attractive aesthetics with the latest T5 fluorescent tube and electronic ballast technology to provide functional and energy saving fittings with the option of automatic self test and dropped legend accessory.

- Offices
- Hospitals
- Public Buildings
- Schools
- Shops and stores
- Health Centres

FEATURES	BENEFITS
<ul style="list-style-type: none"> • R8MUST provides a Self Test Function <ul style="list-style-type: none"> • Complies with BSEN 62034 2006 • 15 minute test once a week • 3 hour test once every 6 months • 3 LED indicators to provide fitting status, condition and any problems for rectification 	<ul style="list-style-type: none"> • Reduced maintenance • British & European standard for self test systems • Simple automatic emergency test function • Ensures the tests are carried out • No wiring required to E-test key switch • No one required to carry out tests • Time and cost saving • No damage to decor in retrofit installations
<ul style="list-style-type: none"> • Surface or recessed three-in-one fitting <ul style="list-style-type: none"> • Bulkhead • Exit box using supplied legends • Blade Dropped Legend 	<ul style="list-style-type: none"> • Provides solutions for all application in a complete building installation
<ul style="list-style-type: none"> • Polycarbonate body and clip on cover 	<ul style="list-style-type: none"> • Strong damage resistant material for long life • Fast and simple access for connection and installation • Quick lamp change access when required • Provides easy dropped legend conversion
<ul style="list-style-type: none"> • First fix base with 2nd fix push fit body 	<ul style="list-style-type: none"> • No damage to main body whilst decorating
<ul style="list-style-type: none"> • Standard T5 8W tube included 	<ul style="list-style-type: none"> • Ready to install • Rated life of 10,000 hours for low maintenance
<ul style="list-style-type: none"> • Blade dropped legend accessory 	<ul style="list-style-type: none"> • Provides exit route direction viewable from 32m
<ul style="list-style-type: none"> • C/w NiCad rechargeable battery 	<ul style="list-style-type: none"> • Provides 3 hour emergency operation
<ul style="list-style-type: none"> • Maintained or non-maintained operation 	<ul style="list-style-type: none"> • Provides illumination as a standard maintained/switched fitting or can be wired to provide emergency lighting only when mains power fails
<ul style="list-style-type: none"> • 2 year guarantee 	<ul style="list-style-type: none"> • A quality energy efficient long life product • Peace of mind

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE