


# Metallic conduit systems

## Type SPUL & A - Adaptasteel



Type SPUL  
Covered Steel Flexible Conduit

### Type SPUL - Adaptasteel

Liquid Tight UL Listed & CSA Approved Covered Steel Flexible Conduit

**Materials:** PVC Covered Galvanised Steel with Copper Packing / **Colour:** Grey (GR) Only

Part No.	Nominal Conduit Size	Outside Diameter	US Conduit Size	Inside Diameter	Min. Bend Radius	Reel Length
SPUL16	16mm	17.8mm	3/8"	12.5mm	50mm	50m
SPUL20	20mm	21.1mm	1/2"	15.9mm	80mm	50m
SPUL25	25mm	26.4mm	3/4"	21.0mm	110mm	25m
SPUL32	32mm	33.1mm	1"	26.7mm	145mm	25m
SPUL40	40mm	41.8mm	1 1/4"	35.4mm	180mm	25m
SPUL50	50mm	47.9mm	1 1/2"	40.4mm	240mm	25m
SPUL63	63mm	59.7mm	2"	51.6mm	345mm	10m

To order quote part number & reel length, e.g. SPUL16/50M

### Approvals



IP Rating	Appropriate Fitting	Temperature Range	UV Resistance
<b>For use with:</b> Type SPL		Static Applications: -20°C to +75°C	High
IP40	N/A	Moving Applications: -5°C to +105°C	
IP65	N/A	<b>Flexibility &amp; Fatigue Life</b>	
IP66	Type SPL - Type M & C90	Medium Flexibility - Medium Fatigue Life	
IP67	Type SPL - Type A, B, & M	<b>Fire Performance &amp; EMI Screen</b>	
IP68	Type SPL - Type M	Self Extinguishing	
IP69K	Type SPL - Type M		



Type A  
Straight Fitting

### Type A - Adaptasteel

Straight Fitting - Fixed External Male Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

**Materials:** Nickel plated brass

Part No.	Nominal Conduit Size	US Conduit Size	Metric Thread
SPL16/M16/A	16mm	3/8"	M16
SPL16/M20/A	16mm	3/8"	M20
SPL20/M20/A	20mm	1/2"	M20
SPL25/M25/A	25mm	3/4"	M25
SPL32/M32/A	32mm	1"	M32

### Approvals



IP Rating	Appropriate Conduit	Temperature Range
<b>For use with:</b> Type SPL / SPLHC / SPUL		Static Applications: -65°C to +150°C
IP40	N/A	Moving Applications: -45°C to +150°C
IP65	N/A	
IP66	N/A	
IP67	Yes	
IP68	N/A	
IP69K	N/A	