


Metallic conduit systems

Type M & F - Adaptasteel



3

Type M
Straight Swivel Fitting

Type M - Adaptasteel

Straight Swivel Fitting - External Male Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PG Thread
SP12/M16/M	12mm	M16	SP12/PG9/M	12mm	PG9
SP16/M16/M	16mm	M16	SP16/PG11/M	16mm	PG11
SP16/M20/M	16mm	M20	SP16/PG13/M	16mm	PG13.5
SP20/M20/M	20mm	M20	SP20/PG16/M	20mm	PG16
SP25/M25/M	25mm	M25	SP25/PG21/M	25mm	PG21
SP32/M32/M	32mm	M32	SP32/PG29/M	32mm	PG29
SP40/M40/M	40mm	M40			
SP50/M50/M	50mm	M50			

Part No.	Nominal Conduit Size	NPT Thread
SP16/038/M	16mm	3/8"
SP16/038/M	16mm	3/8"
SP20/050/M	20mm	1/2"
SP25/075/M	25mm	3/4"
SP32/100/M	32mm	1"

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SP / SN / LFH-SP		Static Applications: -50°C to +150°C
IP54	N/A	Moving Applications: -45°C to +150°C
IP65	Yes	
IP66	N/A	
IP67	N/A	
IP68	N/A	
IP69K	N/A	

Fitting Characteristics



Type F
Straight Fitting

Type F - Adaptasteel

Straight Fitting - Fixed Internal Female Thread / For external threads and other fittings

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	Metric Thread
SP20/M20/F	20mm	M20
SP25/M25/F	25mm	M25
SP32/M32/F	32mm	M32

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SP / SN / LFH-SP		Static Applications: -50°C to +300°C
IP54	Yes	Moving Applications: -45°C to +250°C
IP65	N/A	
IP66	N/A	
IP67	N/A	
IP68	N/A	
IP69K	N/A	