

Metallic conduit systems

Type C & E - Adaptasteel



Type C
Smooth Entry Bush

Type C - Adaptasteel

Smooth Entry Bush / For locking conduit into plain holes in enclosures

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	Hole Size
SP10/9/C	10mm	9mm
SP12/12/C	12mm	12mm
SP16/16/C	16mm	16mm
SP20/20/C	20mm	20mm
SP25/25/C	25mm	25mm
SP32/32/C	32mm	32mm
SP40/40/C	40mm	40mm
SP50/51/C	50mm	51mm
SP63/61/C	63mm	61mm
SP75/75/C	75mm	75mm

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SP / SN / LFH-SP		
IP54	Yes	Static Applications: -50°C to +300°C Moving Applications: -45°C to +250°C
IP65	N/A	
IP66	N/A	
IP67	N/A	
IP68	N/A	
IP69K	N/A	



Type E
Conduit Terminator

Type E - Adaptasteel

Conduit Terminator / Cable Protection at exit point

Materials: Nickel plated brass

Part No.	Nominal Conduit Size
SP12/E	12mm
SP16/E	16mm
SP20/E	20mm
SP25/E	25mm
SP32/E	32mm
SP40/E	40mm
SP50/E	50mm

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SP / SN / LFH-SP		
IP54	Yes	Static Applications: -50°C to +300°C Moving Applications: -45°C to +250°C
IP65	N/A	
IP66	N/A	
IP67	N/A	
IP68	N/A	
IP69K	N/A	