


Metallic conduit systems

Type B & C90 - Adaptasteel



Type B
Straight Fitting

Type B - Adaptasteel

Straight Fitting - Swivel External Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PG Thread
SP10/M12/B	10mm	M12	SP10/PG7/B	10mm	PG7
SP12/M16/B	12mm	M16	SP12/PG9/B	12mm	PG9
SP16/M16/B	16mm	M16	SP16/PG11/B	16mm	PG11
SP16/M20/B	16mm	M20			
SP20/M20/B	20mm	M20	SP20/PG16/B	20mm	PG16
SP25/M25/B	25mm	M25	SP25/PG21/B	25mm	PG21
SP32/M32/B	32mm	M32	SP32/PG29/B	32mm	PG29
SP40/M40/B	40mm	M40	SP40/PG36/B	40mm	PG36
SP50/M50/B	50mm	M50	SP50/PG42/B	50mm	PG42

Approvals



IP Rating

Appropriate Conduit

For use with: Type SP / SN / LFH-SP

IP54	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69K	N/A

Temperature Range

Static Applications: -50°C to +300°C
Moving Applications: -45°C to +250°C

Fitting Characteristics



Type C90
90° Combined Fitting & Elbow

Type C90 - Adaptasteel

90° Combined Fitting & Elbow / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	Metric Thread
SP16/M16/C90	16mm	M16
SP16/M20/C90	16mm	M20
SP20/M20/C90	20mm	M20
SP25/M25/C90	25mm	M25
SP32/M32/C90	32mm	M32

Approvals



IP Rating

Appropriate Conduit

For use with: Type SP / SN / LFH-SP

IP54	N/A
IP65	Yes
IP66	N/A
IP67	N/A
IP68	N/A
IP69K	N/A

Temperature Range

Static Applications: -50°C to +300°C
Moving Applications: -45°C to +250°C

Fitting Characteristics

