

Non-metallic conduit systems

Type A - Adaptalok

2



Type A
Straight Fitting

Type A - Adaptalok

Straight Fitting - Fixed External Male Thread / For insertion into knockouts using a locknut. Locknut supplied with METRIC THREAD ONLY

Materials: Polyamide (Nylon) 66 / **Colour:** Black (BL), Grey (GR)

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PG Thread
AL10/M12/A	10mm	M16	AL10/PG7/A	10mm	PG7
			AL10/PG9/A	10mm	PG9
AL13/M16/A	13mm	M16	AL13/PG9/A	13mm	PG9
AL13/M20/A	13mm	M20	AL13/PG11/A	13mm	PG11
			AL13/PG13/A	13mm	PG13.5
AL16/M16/A	16mm	M16	AL16/PG9/A	16mm	PG9
AL16/M20/A	16mm	M20	AL16/PG11/A	16mm	PG11
			AL16/PG13/A	16mm	PG13.5
			AL16/PG16/A	16mm	PG16
AL21/M20/A	21mm	M20	AL21/PG11/A	21mm	PG11
			AL21/PG13/A	21mm	PG13.5
AL21/M25/A	21mm	M25	AL21/PG16/A	21mm	PG16
AL28/M25/A	28mm	M25	AL28/PG21/A	28mm	PG21
AL28/M32/A	28mm	M32			
AL34/M32/A	34mm	M32	AL34/PG29/A	34mm	PG29
AL34/M40/A	34mm	M40			
AL42/M40/A	42mm	M40	AL42/PG36/A	42mm	PG36
AL42/M50/A	42mm	M50			
AL54/M50/A	54mm	M50	AL54/PG48/A	54mm	PG48
AL54/M63/A	54mm	M63			

Part No.	Nominal Conduit Size	PF Thread	Part No.	Nominal Conduit Size	NPT Thread
AL10/PF025/A	10mm	1/4"	AL13/038/A	13mm	3/8"
AL13/PF038/A	13mm	3/8"	AL16/038/A	16mm	3/8"
AL16/PF038/A	16mm	3/8"	AL16/050/A	16mm	1/2"
AL16/PF050/A	16mm	1/2"	AL21/050/A	21mm	1/2"
AL21/PF050/A	21mm	1/2"	AL28/075/A	28mm	3/4"
AL28/PF075/A	28mm	3/4"	AL34/100/A	34mm	1"
AL34/PF100/A	34mm	1"	AL42/125/A	42mm	1 1/4"
AL42/PF125/A	42mm	1 1/4"	AL54/150/A	54mm	1 1/2"
AL54/PF150/A	54mm	1 1/2"			
AL54/PF200/A	54mm	2"			

To order quote part number & body colour, e.g. AL10/M12/A/BL

Approvals



IP Rating

Appropriate Conduit

For use with: Type PA / PI / CP / PR / PF

IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69K	Yes + ALS Seal

Temperature Range

Static Applications: -50°C to +120°C

Moving Applications: -45°C to +120°C

Fitting Characteristics

