

Metallic conduit systems

Type B & E - Adaptasteel

3



Type B
Straight Fitting

Type B - Adaptasteel

Straight Fitting - Swivel External Male Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	US Conduit Size	Metric Thread
SPL16/M16/B	16mm	3/8"	M16
SPL16/M20/B	16mm	3/8"	M20
SPL20/M20/B	20mm	1/2"	M20
SPL25/M25/B	25mm	3/4"	M25
SPL32/M32/B	32mm	1"	M32

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SPL / SPLHC / SPUL		Static Applications: -65°C to +150°C
IP54	N/A	Moving Applications: -45°C to +150°C
IP65	N/A	
IP66	N/A	
IP67	Yes	
IP68	N/A	
IP69K	N/A	

Fitting Characteristics



Type E
Conduit Terminator

Type E - Adaptasteel

Conduit Terminator / Cable protection at exit point

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	US Conduit Size	Metric Thread
SPL10/E	10mm	1/4"	M16
SPL12/E	12mm	5/16"	M20
SPL16/E	16mm	3/8"	M20
SPL20/E	20mm	1/2"	M25
SPL25/E	25mm	3/4"	M25
SPL32/E	32mm	1"	M20
SPL40/E	40mm	1 1/4"	M20
SPL50/E	50mm	1 1/2"	M25
SPL63/E	63mm	2"	M32

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SPL / SPLHC / SPUL		Static Applications: -65°C to +300°C
IP54	Yes	Moving Applications: -45°C to +250°C
IP65	N/A	
IP66	N/A	
IP67	N/A	
IP68	N/A	
IP69K	N/A	