

Metallic conduit systems

Type C90 & 45 - Adaptasteel



Type A
90° Combined
Fitting & Elbow

3

Type C90 - Adaptasteel

90° Combined Fitting & Elbow - Swivel External Male Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	US Conduit Size	Metric Thread
SPL16/M16/C90	16mm	3/8"	M16
SPL16/M20/C90	16mm	3/8"	M20
SPL20/M20/C90	20mm	1/2"	M20
SPL25/M25/C90	25mm	3/4"	M25
SPL32/M32/C90	32mm	1"	M32

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SPL / SPLHC / SPUL		Static Applications: -65°C to +150°C
IP54	N/A	Moving Applications: -45°C to +150°C
IP65	N/A	
IP66	N/A	
IP67	Yes	
IP68	N/A	
IP69K	N/A	



Type 45
45° Elbow

Type 45 - Adaptasteel

45° Elbow - Fixed External Male Thread / For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Materials: Nickel plated brass

Part No.	Nominal Conduit Size	US Conduit Size	Metric Thread
B/M16/45	16mm	3/8"	M16*
B/M20/45	16mm	3/8"	M20
B/M20/45	20mm	1/2"	M20
B/M25/45	25mm	3/4"	M25
B/M32/45	32mm	1"	M32

*Includes M20 Internal Thread

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type SPL / SPLHC / SPUL		Static Applications: -65°C to +150°C
IP54	N/A	Moving Applications: -45°C to +150°C
IP65	N/A	
IP66	N/A	
IP67	Yes	
IP68	N/A	
IP69K	N/A	