



LEDPRO10



LEDPRO20



LEDPRO30



LEDPRO50



LEDPROSL



LEDPROPC

### LEDPRO10B

10W Professional Rewireable Floodlight – 650 lumens

- Rewireable with easy access screw terminals with link terminal for common accessories control.
- 10W LED power – instantly bright like halogens but at a fraction of the running costs.
- 650 lumens of cool white light (colour 5000k).
- Polycarbonate front lens with prismatic centre for enhanced light control.
- Fully polycarbonate front lens ideal for food preparation areas and grain stores.
- Plug & Play PIR option with linkable control (optional extra).
- Plug & Play Photocell option with linkable control (optional extra).
- Easy install bracket – enables floodlight fixing screws to be pre-fitted.
- Installer friendly captive terminal cover screws 2x PG11 glands supplied, suitable for 1.5mm twin and earth flat cable.
- IP65 weatherproof rating.
- Driverless ACLED technology.
- Long life – up to 30,000 hours for low maintenance.
- UK and European registered design.

### LEDPRO10WH

White Version – 750 lumens

- 10W LED power – instantly bright like halogens but at a fraction of the running costs.
- 750 lumens of cool white light (colour 5000k).

### LEDPRO20B

20W Professional Rewireable Floodlight – 1400 lumens

- 20W LED power – instantly bright like halogens but at a fraction of the running costs.
- 1400 lumens of cool white light (colour 5000k).
- Plug & Play PIR option with linkable control (optional extra).
- Plug & Play Photocell option with linkable control (optional extra).
- IP65 weatherproof rating.

### LEDPRO20WH

White Version – 1500 lumens

- 20W LED power – instantly bright like halogens but at a fraction of the running costs.
- 1500 lumens of cool white light (colour 5000k).

### LEDPRO30B

30W Professional Rewireable Floodlight – 2050 lumens

- 30W LED power – instantly bright like halogens but at a fraction of the running costs.
- 2050 lumens of cool white light (colour 5000k).
- Plug & Play PIR option with linkable control (optional extra).
- Plug & Play Photocell option with linkable control (optional extra).
- IP65 weatherproof rating.

### LEDPRO30WH

White Version – 2100 lumens

- 30W LED power – instantly bright like halogens but at a fraction of the running costs.
- 2100 lumens of cool white light (colour 5000k).



All these products carry a 3 year guarantee.



See page 91 for product specifications.

### LEDPRO50B

50W Professional Rewireable Floodlight – 3500 lumens

- 50W LED power – instantly bright like halogens but at a fraction of the running costs.
- 3500 lumens of cool white light (colour 5000k).
- Plug & Play PIR option with linkable control (optional extra).
- Plug & Play Photocell option with linkable control (optional extra).
- IP65 weatherproof rating.

### LEDPRO50WH

White Version – 3600 lumens

- 50W LED power – instantly bright like halogens but at a fraction of the running costs.
- 3600 lumens of cool white light (colour 5000k).

### LEDPROSLB

Dedicated PIR Detector for LEDPRO Range

Simply replaces the terminal cover and plugs into the LEDPRO Floodlight offering a 140W LED PIR with a 180° 12m detection range. Features include tilt and rotate adjustable head, timed on adjustable control and manual override.

- Dedicated 140W LED PIR for use with Timeguard LEDPRO floodlights.
- Maximum Switchable Load: LED lamp –140W; halogen lamp – 1000W; CFL – 200W; fluorescent tube w/o PF correction – 500W.
- Simply replaces the terminal cover and plugs in to the LEDPRO floodlight – no extra cabling necessary.
- Installer friendly captive terminal cover screws 2x cable entries suitable for PG11 gland (glands not supplied).
- 12 metre, 180° detection.
- Tilt and rotate adjustable head for accurate reliable detection.
- 3 seconds – 18 minutes timed duration (adjustable).
- Photocell sensor (adjustable) and manual override function.
- IP55 weatherproof rating.

### LEDPROSLWH

White Version

### LEDPROPCB

Dedicated Photocell for LEDPRO Range

Has the same terminal link options and allows 2, 4, 6 or 8 hours timed on duration or continuous dusk to dawn settings.

- Dedicated 140W LED Photocell for use with Timeguard LEDPRO Floodlights.
- Maximum Switchable Load: LED lamp –140W; halogen lamp – 1000W; CFL – 200W; fluorescent tube w/o PF correction – 500W.
- Installer friendly captive terminal cover screws 2x cable entries suitable for PG11 gland (glands not supplied).
- Simply replaces the terminal cover and plugs in to the LEDPRO floodlight – no extra cabling necessary.
- 2, 4, 6 or 8 hours timed on duration or continuous Dusk to Dawn (adjustable).
- Adjustable LUX setting.
- IP55 weatherproof rating.

### LEDPROPCWH

White Version



Night Eye Plus Floodlights are a unique Timeguard registered design offering stand alone IP65 floodlight installation or optional Plug & Play PIR and Photocell linkable controls to fit all variants.

The range of 10W, 20W, 30W and 50W LED Floodlights are completely rewireable with easy accessible screw terminals and link terminal for common accessories control.

The polycarbonate front lens has a prismatic centre for enhanced LED lighting control, making them ideal for specific area uses such as food preparation areas or grain control.



Simply plugs into the terminal box offering a 140W LED PIR and Photocell option. One size fits all floodlights.



LEDPRO20B Floodlight shown with LEDPROSLB Plug & Play PIR option.

### Product Features



Curved slim design.



Polycarbonate front lens with prismatic centre for enhanced light control.



Cooling fins prevent heat build-up for long product life.



Plug & Play PIR option with linkable control (sold separately).



Plug & Play Photocell option with linkable control (sold separately).



Simple and quick to fit terminal block connection.