

# RCD.Sockets - Switched



**-PowerBreaker-** THE FIRST SINCE 1975

The K range RCD switched sockets are available in single or twin outlets, in white or metalclad with mechanical latching. These sockets replace standard sockets to provide added protection against electrocution in commercial, domestic and industrial environments.

- Mechanically latched (does not need resetting after a power loss)
- High intensity LED power on indicator, clear visual indicator of power on
- Twin sockets fitted with twin earth terminals

## Technical Data

Rated voltage	230V AC 50Hz
Max operating current	13A (13A inductive)
Rated trip current	30mA
Typical trip speed	Less than 20mS (typical)
RCD contact break	Double pole
Latching	Mechanical, no need to reset after power loss (passive)
Responsive to	Pulsating DC earth faults
Conforms to	BS 7288:1990, Amd 1 and BS 1363-2:1995 Amd 1-3
EMC Emissions	EN 55014-1:2006 & EN 55014-1:2000 inc A1:2001 & A2:2002
EMC Immunity	EN 61543:1995 inc A11:2003, A12:2005 & A2:2006

PART NO.	DESCRIPTION	COLOUR	
<b>K21WPA-C</b>	RCD Single Switched Socket Slim profile Moulded front plate Fits standard 25mm back box	White	
<b>K22WPA-C</b>	RCD Twin Switched Socket Slim profile Moulded front plate Fits standard 25mm back box		
<b>K22SPA</b>	Panel Mounting RCD Twin Switched Socket Moulded front plate See H22SPA Max Plate Thickness 2mm		