

## SPECIFICATION SHEET

Product Code

DP\*535#

Description

13A 1 Gang DP 'Ingot' Switched Socket Outlet



| General Information   |   |
|---|---|
| Dimensions  | 88mm x 88mm x 8mm (Excluding Gasket)  |
| Finishes Available  | Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel)                               |
| Inserts Available   | Replace # with: WH (White) or BK (Black).<br>Black or White gasket supplied to match appropriate insert.<br>(Antique Brass and Black Nickel are only available with black inserts)          |
| Material composition  | Front Plate: Stainless Steel<br>Rear Housing: Urea<br>Terminals: Brass<br>Earth Strap: Mild Steel<br>Terminal Screws: Steel and Yellow Passivated<br>Silver "on-lay" copper/brass contacts. |
| Voltage   | 250V~ 50Hz  |
| Load Rating   | 13A   |
| Terminal Size   | 5mm Ø   |
| Torque Value  | 2.5Nm   |
| Cable Size  | 4 x 2.5mm <sup>2</sup>  |
| Back Box Depth  | 25mm – 47mm   |
| Switched  | Yes   |
| Double Pole   | Yes   |
| Twin Earth Terminals  | No  |
| Clean Earth Terminals   | No  |
| Operational Temperature   | -5°C – +40°C  |
| Warranty  | 10 Years  |
| Standards   |   |
| BS 1363-2: 1995 + A4: 2012  |   |
| Additional Information  |   |
| Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.<br>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |   |

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0