

SPECIFICATION SHEET

Product Code

DP*751#

Description

13A Fused Connection Unit Switched
'Ingot'



General Information	
Dimensions	88mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel)
Inserts Available	Replace # with: WH (White) or BK (Black). Black or White gasket supplied to match appropriate insert. (Antique Brass and Black Nickel are only available with black inserts)
Material composition	Front Plate: Stainless Steel Rear Housing: Urea Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Voltage	240V~ 50Hz
Load Rating	13A
Terminal Size	5mm Ø
Torque Value	2.5Nm
Cable Size	3 x 2.5mm ² or 2 x 4mm ²
Back Box Depth	25mm – 47mm
Switched	Yes
Double Pole	Yes
Twin Earth Terminals	Yes
Flex Outlet	No
Neon Indicator	No
Operational Temperature	-5°C – +40°C
Warranty	10 Years
Standards	
BS 1363-4: 1995 + A4: 2012 BS 1362: 1973 (Fuse)	
Additional Information	
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.	

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0