



FHDVC550VFB

5-50mm Lens 1080P HD Camera



- 5 to 50mm Varifocal Lens
- High Definition 2MP AHD sensor
- Built in 50m Infrared LED Illumination
- D-WDR incorporating ATR
- 2D and 3D Noise Reduction
- Exposure Control
- High Light Compensation
- 3-Axis Cable Management Bracket
- IP66 Weatherproof Bullet Housing

Sensor Size	1/2.7"
Effective Pixels	NTSC/ PAL:1920(H)x1080(V)
Resolution	1080P
Minimum Illumination	0.1 Lux/F1.6 0 Lux (with IR LED ON)
Scanning System	Progressive
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/100,000s
IR Distance	50 Meters
Video Output	1Vpp, 75 ohms
Auto Gain Control	Auto
Power/Current	DC12V(+/-10%)/560mA
Lens	5-50mm Manual Zoom Lens
Dimension	260(L) x 136(H) x 115(D)mm
Weight	1200g
Storage Temperature	-30 ~ +60°C RH95% Max
Operating Temperature	-10 ~ +50°C RH95% Max



FHDVC622VFB

6-22mm Lens 1080P HD Camera



- 6 to 22mm Varifocal Lens
- High Definition 2MP AHD sensor
- Built in 50m Infrared LED Illumination
- D-WDR incorporating ATR
- 2D and 3D Noise Reduction
- Exposure Control
- High Light Compensation
- 3-Axis Cable Management Bracket
- IP66 Weatherproof Bullet Housing

Sensor Size	1/2.7"
Effective Pixels	NTSC/ PAL:1920(H)x1080(V)
Resolution	1080P
Minimum Illumination	0.1 Lux/F1.6 0 Lux (with IR LED ON)
Scanning System	Progressive
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/100,000s
IR Distance	50 Meters
Video Output	1Vpp, 75 ohms
Auto Gain Control	Auto
Power/Current	DC12V(+/-10%)/560mA
Lens	6-22mm Manual Zoom Lens
Dimension	260(L) x 136(H) x 115(D)mm
Weight	1200g
Storage Temperature	-30 ~ +60°C RH95% Max
Operating Temperature	-10 ~ +50°C RH95% Max