

- Simple 2 core cable installation
- Single power supply (included) supports all monitors and outdoor stations in a flexible combination of up to 5 devices
- Clear high resolution colour picture on 7" hands free TFT monitor

Station

| | |
|-------------------|----------------------------|
| Image sensor | 1/3" Colour CCD |
| Min. Illumination | 0.1 LUX |
| Illumination | 6 LEDs |
| Lens | 3.6mm |
| Power | 24VDC |
| Operating Temp. | -20°C ~ +40°C |
| Dimensions | 85mm(W)x 165mm(H)x 53mm(D) |
| Weight | 390g |

Monitor

| | |
|-------------------|---------------------------|
| Power | 24VDC |
| Installation | Surface Mounted |
| Operational Temp. | 0°C ~ +40°C |
| Consumption | 350mA |
| Dimensions | 183mm(W)x185mm(H)x20mm(D) |
| Weight | 550g |



C/W White Monitor

APKITG

C/W Black Monitor

APKITGBLK

Colour Video Door Entry System with Record Facility

- Simple 2 core cable installation
- Single power supply (included) supports all monitors and outdoor stations in a flexible combination of up to 5 devices
- Clear high resolution colour picture on 7" hands free TFT monitor
- Outdoor station with built in keypad for code door unlocking

Station

| | |
|-------------------|----------------------------|
| Image sensor | 1/3" Colour CCD |
| Min. Illumination | 0.1 LUX |
| Illumination | 6 LEDs |
| Lens | 3.6mm |
| Power | 24VDC |
| Operating Temp. | -20°C ~ +40°C |
| Dimensions | 87mm(W)x 200mm(H)x 53mm(D) |
| Weight | 640g |

Monitor

| | |
|-------------------|---------------------------|
| Power | 24VDC |
| Installation | Surface Mounted |
| Operational Temp. | 0°C ~ +40°C |
| Consumption | 350mA |
| Dimensions | 183mm(W)x185mm(H)x20mm(D) |
| Weight | 550g |



C/W White Monitor

APKITKPG

C/W Black Monitor

APKITKPGBLK

Colour Video Door Entry Keypad System with Record Facility