
Conduit Fixing Accessories

properties

- Suitable for use with flexible and pliable conduits
- Clips and F-Clamps manufactured from nylon PA66
- Temperature Range -50° to 135°
- UV resistant

- Low Fire Hazard see page 102
- Halogen, Sulphur & Phosphorous Free
- Self extinguishing
- For installation instructions see page 100





Fittings

			NEW	NEW	NEW	NEW	NEW
	condu clips	ıit	FCLAMP	FCLAMP- CP	FCLAMP- WP	FCLAMP- EWP	FCLAMP- BOLT
с ir	nylon conduit clip with integral lid - black or grey		non-metallic, heavy duty conduit clamp Nylon PA66, conduit fixing clamp for corrugated conduit.	plated steel cover plate for use with FCLAMP	plated steel weld plate to fix FCLAMP	plated steel elongated weld plate to fix FCLAMP	fixing bolts to secure FCLAMPS For information on stacking bolts consult our website.
		0	0		00	-0 01	3
Conduit size (mm)	conduit clip for corrugated	conduit clip for plain or rigid	part number	part number	part number	part number	part number
10	FCL10						
13	FCL13						
16	FCL16 FCL18	FCL16B-P FCL18B-P	FCLAMP-3-16	FCLAMP-CP3	FCLAMP-WP3	FCLAMP-EWP3	FCLAMP-BOLT3
18 20	FCL18	FCL10B-P					
21	FCL21	FCL21B-P	FCLAMP-3-21	FCLAMP-CP3	FCLAMP-WP3	FCLAMP-EWP3	FCLAMP-BOLT3
25	FCL25	FCL25B-P					
26		FCL26B-P					
28	FCL28		FCLAMP-4-28	FCLAMP-CP4	FCLAMP-WP4	FCLAMP-EWP4	FCLAMP-BOLT4
32		FCL33B-P					
34	FCL34		FCLAMP-5-34	FCLAMP-CP5	FCLAMP-WP5	FCLAMP-EWP5	FCLAMP-BOLTS
42 54	FCL42 FCL54		FCLAMP-6-42 FCLAMP-7-54	FCLAMP-CP6 FCLAMP-CP7	FCLAMP-WP6 FCLAMP-WP7	FCLAMP-EWP6 FCLAMP-EWP7	FCLAMP-BOLT6 FCLAMP-BOLT7
54 67	FUL04		FCLAMP-7-67	FCLAMP-CP7	FCLAMP-WP7	FCLAMP-EWP7	FCLAMP-BOLT7
80			FCLAMP-8-80	FCLAMP-CP8	FCLAMP-WP8	FCLAMP-EWP8	FCLAMP-BOLT8

mounting rail

mounting rail fix	ng accessories
-------------------	----------------

suitable for mounting FCL & FCL-P used to fix positions of FCL clips and F-Clamps conduit clips and F-CLAMPS. on mounting rail and prevent movement. Universal channel rail adaptor - suitable for mounting F-Clamps Supplied in 0.6m, 1.2m or 2.4m lengths. when used with channel rails such as Unistrut®, Halfen and Hilti. For rail dimensions or for other lengths consult us or visit our website. MRFAL size stainless steel aluminium galv steel plastic material MRFALSS MRSSA-# MRAA-# MRGSA-# MRPA-# stainless steel a MRSSB-# MRAB-# MRGSB-# MRPB-# aluminium MRFALA b MRSSC-# MRPC-# MRFALNPB MRAC-# MRGSB-# nickel plated brass C

nickel plated steel

NEW

MRFAM MRFAH MRFAMSS

MRFAMA MRFAMNPB

MRFAHSS MRFAHA **MRFAHNPB**

MRFAU

UNIVERSA

NEW

- enter desired length e.g 1.2m #=1.2M For stacking arrangements of our F-Clamps visit our website for further details

See page 100 for installation instructions