


A9 ... A75 4-pole Contactors - a.c. Coil

Ordering Details



A 9-40-00



A 45-40-00



A 9-22-00

Rated operational current AC-1 $\theta \leq 40\text{ }^{\circ}\text{C}$ A	Auxiliary contacts fitted 	Type State coil voltage:	Order code coil voltage code see table below : ☐ ☐	Weight kg	Pack ^{ing} 1 piece
--	-------------------------------	---	--	---------------------	--------------------------------

4-pole Contactors - 4 NO Main Poles

25	- -	A 9-40-00	1SBL 14 1201 R ☐ ☐ 00	0.340
30	- -	A 16-40-00	1SBL 18 1201 R ☐ ☐ 00	0.340
45	- -	A 26-40-00	1SBL 24 1201 R ☐ ☐ 00	0.610
70	- -	A 45-40-00	1SBL 33 1201 R ☐ ☐ 00	1.390
100	- -	A 50-40-00	1SBL 35 1201 R ☐ ☐ 00	1.390
125	- -	A 75-40-00	1SBL 41 1201 R ☐ ☐ 00	1.390

4-pole Contactors - 2 NO + 2 NC Main Poles

25	- -	A 9-22-00	1SBL 14 1501 R ☐ ☐ 00	0.340
30	- -	A 16-22-00	1SBL 18 1501 R ☐ ☐ 00	0.340
45	- -	A 26-22-00	1SBL 24 1501 R ☐ ☐ 00	0.610
70	- -	A 45-22-00	1SBL 33 1501 R ☐ ☐ 00	1.400
125	- -	A 75-22-00	1SBL 41 1501 R ☐ ☐ 00	1.400

Coil voltages and codes: A9 ... A75

Voltage (V) 50 Hz :	Voltage (V) 60 Hz :	Voltage code : ☐ ☐
24	24	☐ 1
48	48	☐ 3
110	110...120	☐ 4
220 ... 230	230...240	☐ 0
230 ... 240	240...260	☐ 8
380 ... 400	400...415	☐ 5
400 ... 415	415...440	☐ 6

Other voltages : page 36.

>> Accessories page 18

>> Dimensions page 51

>> Technical data page 34