AF09 ... AF38 3-pole contactors
4 to 18.5 kW
AC / DC operated

AF09-30-10

AF26-30-00

5

Description

AF09 ... AF38 contactors are mainly used for controlling 3-phase motors and power circuits up to 690 V AC and 220 V DC. These contactors are of the block type design with 3 main poles.

– control circuit: AC or DC operated with electronic coil interface accepting a wide control voltage range (e.g. 100...250 V AC and DC), only 4 coils to cover control voltages between 24...500 V 50/60 Hz and 20...500 V DC
  - can manage large control voltage variations
  - reduced panel energy consumption
  - very distinct closing and opening.
– built-in surge suppression
– add-on auxiliary contact blocks for front or side mounting and a wide range of accessories.

Ordering details

IEC		UL/CSA		Rated control circuit voltage Uc min. ... Uc max.		Auxiliary contacts fitted		Type	Order code		Weight
Rated operational power 400 V AC-3	current θ ≤ 40 °C AC-1	3-phase motor rating 480 V	General use rating 600 V AC								Pkg (1 pce)
kW	A	hp	A	V 50/60 Hz	V DC						kg
4	25	5	25	24...60	20...60 (1)	1	0	AF09-30-10-11	1SBL137001R1110		0.270
						0	1	AF09-30-01-11	1SBL137001R1101		0.270
				48...130	48...130	1	0	AF09-30-10-12	1SBL137001R1210		0.270
						0	1	AF09-30-01-12	1SBL137001R1201		0.270
				100...250	100...250	1	0	AF09-30-10-13	1SBL137001R1310		0.270
						0	1	AF09-30-01-13	1SBL137001R1301		0.270
				250...500	250...500	1	0	AF09-30-10-14	1SBL137001R1410		0.310
						0	1	AF09-30-01-14	1SBL137001R1401		0.310
5.5	28	7.5	28	24...60	20...60 (1)	1	0	AF12-30-10-11	1SBL157001R1110		0.270
						0	1	AF12-30-01-11	1SBL157001R1101		0.270
				48...130	48...130	1	0	AF12-30-10-12	1SBL157001R1210		0.270
						0	1	AF12-30-01-12	1SBL157001R1201		0.270
				100...250	100...250	1	0	AF12-30-10-13	1SBL157001R1310		0.270
						0	1	AF12-30-01-13	1SBL157001R1301		0.270
				250...500	250...500	1	0	AF12-30-10-14	1SBL157001R1410		0.310
						0	1	AF12-30-01-14	1SBL157001R1401		0.310
7.5	30	10	30	24...60	20...60 (1)	1	0	AF16-30-10-11	1SBL177001R1110		0.270
						0	1	AF16-30-01-11	1SBL177001R1101		0.270
				48...130	48...130	1	0	AF16-30-10-12	1SBL177001R1210		0.270
						0	1	AF16-30-01-12	1SBL177001R1201		0.270
				100...250	100...250	1	0	AF16-30-10-13	1SBL177001R1310		0.270
						0	1	AF16-30-01-13	1SBL177001R1301		0.270
				250...500	250...500	1	0	AF16-30-10-14	1SBL177001R1410		0.310
						0	1	AF16-30-01-14	1SBL177001R1401		0.310
11	45	15	45	24...60	20...60 (1)	0	0	AF26-30-00-11	1SBL237001R1100		0.310
				48...130	48...130	0	0	AF26-30-00-12	1SBL237001R1200		0.310
				100...250	100...250	0	0	AF26-30-00-13	1SBL237001R1300		0.310
				250...500	250...500	0	0	AF26-30-00-14	1SBL237001R1400		0.350
15	50	20	50	24...60	20...60 (1)	0	0	AF30-30-00-11	1SBL277001R1100		0.310
				48...130	48...130	0	0	AF30-30-00-12	1SBL277001R1200		0.310
				100...250	100...250	0	0	AF30-30-00-13	1SBL277001R1300		0.310
				250...500	250...500	0	0	AF30-30-00-14	1SBL277001R1400		0.350
18.5	50	20	50	24...60	20...60 (1)	0	0	AF38-30-00-11	1SBL297001R1100		0.310
				48...130	48...130	0	0	AF38-30-00-12	1SBL297001R1200		0.310
				100...250	100...250	0	0	AF38-30-00-13	1SBL297001R1300		0.310
				250...500	250...500	0	0	AF38-30-00-14	1SBL297001R1400		0.350

(1) AF..-30-..-11 not suitable for direct control by PLC-output.

Main dimensions mm, *inches*



AF09, AF12, AF16



AF26, AF30, AF38

1SBC101371S0201