

Electronic timers

CT-S range

Ordering details



CT-MVS.21



CT-MXS.22



CT-MFS.21



CT-MBS.22



CT-WBS.22

| Type | Rated control supply voltage | Control input | Remote potentiometer connection | 2nd c/o cont. selectable as inst. contact | Order code | Pack. unit pieces | Price 1 piece | Weight 1 piece kg / lb |
|------|------------------------------|---------------|---------------------------------|---|------------|-------------------|---------------|------------------------|
|------|------------------------------|---------------|---------------------------------|---|------------|-------------------|---------------|------------------------|

Multifunction timers

CT-MVS: 11 functions ¹⁾, 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 3 LEDs – 40 °C

**NEW
EXTENDED
TEMPERATURE**

| | | | | | | | | |
|-----------|----------------|---|----|---|--------------------|---|--|---------------|
| CT-MVS.21 | 24-240 V AC/DC | ■ | 1x | • | 1SVR 630 020 R0200 | 1 | | 0.137 / 0.302 |
|-----------|----------------|---|----|---|--------------------|---|--|---------------|

CT-MVS: 11 functions ¹⁾, 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 2 LEDs

| | | | | | | | | |
|-----------|----------------------------|---|--|--|--------------------|---|--|---------------|
| CT-MVS.22 | 24-48 V DC, 24-240 V AC | ■ | | | 1SVR 630 020 R3300 | 1 | | 0.131 / 0.289 |
| CT-MVS.23 | 380-440 V AC | ■ | | | 1SVR 630 021 R2300 | 1 | | 0.135 / 0.298 |

CT-MVS: 10 functions ²⁾, 10 time ranges (0.05 s- 300 h), 1 c/o contact, 2 LEDs

| | | | | | | | | |
|-----------|----------------------------|---|--|--|--------------------|---|--|---------------|
| CT-MVS.12 | 24-48 V DC, 24-240 V AC | ■ | | | 1SVR 630 020 R3100 | 1 | | 0.101 / 0.223 |
|-----------|----------------------------|---|--|--|--------------------|---|--|---------------|

CT-MXS: 5 functions ³⁾, 2 x 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 2 LEDs

| | | | | | | | | |
|-----------|----------------------------|---|----|--|--------------------|---|--|---------------|
| CT-MXS.22 | 24-48 V DC, 24-240 V AC | ■ | 2x | | 1SVR 630 030 R3300 | 1 | | 0.131 / 0.289 |
|-----------|----------------------------|---|----|--|--------------------|---|--|---------------|

CT-MFS: 10 functions ⁴⁾, 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 3 LEDs – 40 °C

**NEW
EXTENDED
TEMPERATURE**

| | | | | | | | | |
|-----------|----------------|-----|----|---|--------------------|---|--|---------------|
| CT-MFS.21 | 24-240 V AC/DC | □/□ | 1x | • | 1SVR 630 010 R0200 | 1 | | 0.134 / 0.295 |
|-----------|----------------|-----|----|---|--------------------|---|--|---------------|

CT-MBS: 10 functions ⁴⁾, 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 3 LEDs

| | | | | | | | | |
|-----------|----------------------------|---|----|---|--------------------|---|--|---------------|
| CT-MBS.22 | 24-48 V DC, 24-240 V AC | □ | 1x | • | 1SVR 630 010 R3200 | 1 | | 0.129 / 0.284 |
|-----------|----------------------------|---|----|---|--------------------|---|--|---------------|

Impulse and flasher timer

CT-WBS: 7 functions ⁵⁾, 10 time ranges (0.05 s- 300 h), 2 c/o contacts, 2 LEDs

| | | | | | | | | |
|-----------|----------------------------|--|--|--|--------------------|---|--|---------------|
| CT-WBS.22 | 24-48 V DC, 24-240 V AC | | | | 1SVR 630 040 R3300 | 1 | | 0.115 / 0.254 |
|-----------|----------------------------|--|--|--|--------------------|---|--|---------------|

■ Control input with voltage-related triggering

□ Control input with volt-free triggering

¹⁾ Functions: ON-delay, OFF-delay with auxiliary voltage, Impulse-ON, Impulse-OFF with auxiliary voltage, Symmetrical ON- and OFF-delay, Flasher starting with ON or OFF, Star-delta change-over with impulse, Pulse former, Accumulative ON-delay, ON/OFF-function

²⁾ Functions: ON-delay, OFF-delay with auxiliary voltage, Impulse-ON, Impulse-OFF with auxiliary voltage, Symmetrical ON- and OFF-delay, Flasher starting with ON or OFF, Pulse former, Accumulative ON-delay, ON/OFF-function

³⁾ Functions: Select function via DIP switches behind the marker label on the front of the unit, asymmetrical ON- and OFF-delay, Impulse-ON/OFF, Pulse generator starting with ON or OFF, Single pulse generator, ON/OFF-function

⁴⁾ Functions: ON-delay, OFF-delay with auxiliary voltage, Impulse-ON, Impulse-OFF with auxiliary voltage, Symmetrical ON- and OFF-delay, Flasher starting with ON, Flasher starting with OFF, Star-delta change-over with impulse, Pulse former, ON/OFF-function

⁵⁾ Functions: Flasher starting with ON, Flasher starting with OFF, Impulse-ON, ON-delay, fixed impulse with adjustable time delay, Adjustable impulse with fixed time delay, ON/OFF-function

| | | | | | |
|-----------------------|------|----------------------------|------|-------------------------------------|------|
| • Accessories | 1/36 | • Function diagrams | 1/37 | • Connection diagrams..... | 1/46 |
| • Technical data..... | 1/49 | • Technical diagrams | 1/51 | • Wiring notes, Dimensional drawing | 1/52 |