

PLUGS - IP66/IP67

EUREKA Series

216.



226.



							 ANGLED OUTLET	
					16A	32A	16A	32A
					cable gland 10/100 ⁽¹⁾	cable gland 10/40	cable gland 10/100 ⁽²⁾	cable gland 10/40
Poles	Hz.	Volt	Colour	h.				
2P+E	50/60	100-130		4	216.1630 (Δ)	216.3230	226.1630	226.3230
	50/60	200-250		6	216.1633 (Δ)	216.3233	226.1633	226.3233
	50/60	380-415		9	216.1638	216.3238		
	50/60	480-500		7				
	50/60	trasf.		12				
	>300-500	>50		2				
	c.c.	>50-250		3				
	c.c.	>250		8				
3P+E	50/60	100-130		4	216.1631	216.3231		
	50/60	200-250		9	216.1634	216.3234		
	50/60	380-415		6	216.1636	216.3236	226.1636	226.3236
	60	440-460		11				
	50/60	480-500		7				
	50/60	600-690		5				
	50/60	380/440		3				226.32364
	100-300	>50		10				
3P+N+E	>300-500	>50		2				
	50/60	100-130		4	216.1632	216.3232		
	50/60	208-250		9	216.1635	216.3235		
	50/60	346-415		6	216.1637	216.3237	226.1637	226.3237
	50/60	480-500		7				
	50/60	600-690		5				
	60	440-460		11				
	50/60	380/440		3				
	>300-500	>50		2				

⁽¹⁾ 3P+N+E= 10/40

⁽²⁾ 3P+N+E= 10/50

Rated operating voltage >50V
- Approvals: from page 561

-  Screw terminals
-  Insulation perforating terminals
-  Spring terminals

More information on page 36

Accessories
Plugs cover page 45



OPTIMA Series

218.



				FAST WIRING	
					
				16A	32A
				cable gland 10/40	cable gland 10/40
Poles	Hz.	Volt	Colour		
2P+E	50/60	100-130		218.1630 (Δ)	218.3230
	50/60	200-250		218.1633 (Δ)(Δ)	218.3233 (Δ)
	50/60	380-415		218.1638	218.3238
	50/60	480-500		218.16336	218.32336
	50/60	trasf.		218.16333	218.32333
	>300-500	>50		218.16332	218.32332
	c.c.	>50-250		218.16334	218.32334
	c.c.	>250		218.16338	218.32338
3P+E	50/60	100-130		218.1631	218.3231
	50/60	200-250		218.1634	218.3234
	50/60	380-415		218.1636 (Δ) (◊)	218.3236 (Δ) (◊)
	60	440-460		218.16365	218.32365
	50/60	480-500		218.16366	218.32366
	50/60	600-690		218.16367	218.32367
	50/60	380/440		218.16364	218.32364
	100-300	>50		218.16361	218.32361
3P+N+E	>300-500	>50		218.16362	218.32362
	50/60	100-130		218.1632	218.3232
	50/60	208-250		218.1635	218.3235
	50/60	346-415		218.1637 (Δ) (◊)	218.3237 (Δ) (◊)
	50/60	480-500		218.16376	218.32376
	50/60	600-690		218.16377	218.32377
	60	440-460		218.16375	218.32375
	50/60	380/440		218.16374	218.32374
	>300-500	>50		218.16372	218.32372



(◊) Phase inverter
Plugs and flush mounting
appliance inlets with phase
inverter, page 44



(Δ) Transparent grip
Version also available with
transparent grip; just add ".TR"
at the end of the catalogue
number. Example 216.1633.TR



(Δ) Black-coloured
Versions also available in black;
just add ".K" at the end of the
catalogue number.
Example 218.1633.K