

CT1016

General Information

Flow™ 16 Way Lighting Management Box



Material Composition	Front Plate, Back Box, Mounting Plate: Mild Steel Male & Female Connectors: Nylon PA66 Switch Cover: Polycarbonate Terminals: HPb59-1 (CU 59%) Silver Plated Terminal Screws: Steel and Yellow Passivated Dust Covers Provided: Polycarbonate
Voltage	230V~ 50Hz
Current Rating	20A Max
Compatible Connectors	CT102C - 3 Pole Connector (Screw Cable Clamps) CT103C - 3 Pole Connector (Fast-fit Cable Clamps) CT103M - 3 Pole Male Connector (Fast-fit Cable Clamps) CT202C - 4 Pole Connector (Screw Cable Clamps) CT203C - 4 Pole Connector (Fast-fit Cable Clamps) CT203M - 4 Pole Male Connector (Fast-fit Cable Clamps) CT1300 - 3 Pole Switch Adapter CT300 - 4 Pole (1 In 3 Out) HUB Junction Box CT350 - 4 Pole (1 In 2 Out) Splitter
Input / Output	1 Male Input (Supply) to receive Female Connector 1 Female Output to receive Male Connector 2 Female Switch Connections to receive 2 Male Connectors 16 Female Outputs to receive 16 Male Connectors
Warranty	10 Years
IP Rating	IP20
Operational Temperature	-5° to +40°C
Standards	KEMA-KEUR BS 5733 : 2010 + A1 : 2014 BS 8488 : 2009 + A1 : 2010 IEC EN 61535 : 2009 + A1: 2013 + C1: 2014

CT1008

General Information

Flow™ 8 Gang Distribution Hub



Material Composition	Front Plate, Back Box, Mounting Plate: Mild Steel Male & Female Connectors: Nylon PA66 Terminals: HPb59-1 (CU 59%) Silver Plated Terminal Screws: Steel and Yellow Passivated Dust Covers Provided: Polycarbonate
Voltage	230V~ 50Hz
Current Rating	20A Max
Compatible Connectors	CT102C - 3 Pole Connector (Screw Cable Clamps) CT103C - 3 Pole Connector (Fast-fit Cable Clamps) CT103M - 3 Pole Male Connector (Fast-fit Cable Clamps) CT202C - 4 Pole Connector (Screw Cable Clamps) CT203C - 4 Pole Connector (Fast-fit Cable Clamps) CT203M - 4 Pole Male Connector (Fast-fit Cable Clamps) CT1300 - 3 Pole Switch Adapter CT300 - 4 Pole (1 In 3 Out) HUB Junction Box CT350 - 4 Pole (1 In 2 Out) Splitter
Input / Output	1 Male Input (Supply) to receive Female Connector 1 Female Output to receive Male Connector 8 Female Outputs to receive 8 Male Connectors
Switch Configurations	2 Way 8 Gang Configuration 1 Way 8 Gang Configuration
Warranty	10 Years
IP Rating	IP20
Operational Temperature	-5° to +40°C
Standards	KEMA-KEUR BS 5733 : 2010 + A1 : 2014 BS 8488 : 2009 + A1 : 2010 IEC EN 61535 : 2009 + A1: 2013 + C1: 2014