

Xpelair Domestic Accessories



Fire Damper XFC

XFC100 Dia. 100mm **Ref. 89843AA**
XFC125 Dia. 125mm **Ref. 89844AA**
XFC160 Dia. 150mm **Ref. 89845AA**
XFC200 Dia. 200mm **Ref. 89846AA**


- For ducts, walls and ceilings. Should not be fitted into flexible ducting. Wall or duct in which XFC is fitted should have a rated fire integrity in accordance with Building Regulations Part B
- Provides full 1 hour fire check
- Closing temperature 72°C
- Low temperature drop
- Tested at Warrington Fire Research Centre to BS476 Part 20



Vent Cowl VC10

Ref. 89531AA

- Provides weather protection for a 100mm PVCu rigid ducted outlet
- Pushfit and should be secured with solvent adhesive
- Material: PVCu
- Colour: Grey
- Used with: Premier DX180, DX200, DX400, DX100 axial models in exposed situations.
- Cowl diameter: 200mm
- wØ201 x h101 x inner Ø110mm



Glass Mounting Kits GMK & DXDG

Premier glass mounting kit GMK
Ref. 90546AA

- Used for installing Premier DX180, DX200 and CF20 models in a window
- Glass thickness: 4-28mm

DX100 double/triple glazing kit DXDG
Ref. 07439AA

- Allows DX100/LV100 to be mounted in double glazed panels from 6 to 46mm thick



GX Wall Kit WK

For GXC9 models
Ref. 89372AA

For GX6/GXC6 models
Ref. 89370AA

- For bridging cavity walls or lining solid double brick walls
- Steel wall liner. Length 280mm
- Set of 508mm ladder strips
- Ø255mm
- Hole diameter: 267mm



Condensation Trap XCT100

Ref. 89749AA

- For use with 100mm dia ducting
- Prevents condensed water running back down the duct towards the fan in vertical PVCu pipe ducted applications. (Not suitable for use in a flexible duct run)
- Collected water must be piped to a convenient disposal point
- Colour: Grey
- 20mm drain off point
- Material: PVCu
- Length: 85mm



Easy-Fix Termination Kit EFT

Ref. 90427AA

- Designed to be installed from inside a building through a cored out to Ø115mm (nominal) hole drilled in brickwork
- Easily cut to length
- Simple installation save times and cost
- Four sealing rings provide a watertight seal in the external wall
- Used with: Premier DX180, DX200, CF20. Not suitable for 100mm axial fans
- Length: 465mm



Airbrick Adaptor XAA

Ref. 89777AA

- A fabricated G.S.M 340mm sleeve to bridge a cavity and line a solid wall
- Connects to 100mm duct
- Includes an air brick
- GSM adaptor
- Used with all 100mm fans.
- w220 x h65 x d340 Ø100mm



Spigot Plate SP100

Ref. 89697AA

- Connects a duct to the wall face
- 100mm spigot
- Material: Plastic
- Used with: All ducted 100mm fans.
- For larger diameter spigot plates see page 81
- w180 x h180 x Ø96.5



Ceiling Kit XCMK

Ref. 90066AA

- Allows a sealed ceiling mounting of ducted products
- Complete with ceiling adaptor tube 105.7m dia, rubber gasket and foam strip
- Used with: Premier DX180, DX200, DX400