



EMERGENCY LIGHTING



EM2WMEXSIGNU
LED 2W Maintained
Exit Sign Legend UP



EM2WMEXSIGNL
LED 2W Maintained
Exit Sign Legend LEFT



EM2WMEXSIGND
LED 2W Maintained
Exit Sign Legend DOWN



EM2WMEXSIGNR
LED 2W Maintained
Exit Sign Legend RIGHT

EM2WMEXSIGN

LED 2W Maintained Exit Sign

- 6000K colour temperature
- Viewing distance – 24m
- SMD 3528 Lamp
- Polycarbonate frame with legend
- Ceiling or wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 4.8V 600mAH Battery
- BS EN 60598-2-22 Standards
- Dimensions - 305 x 160 x 225mm
- Weight - 0.8Kg



EM9WNMSPOT

LED IP65 Non Maintained Emergency Twin Spot

- 2 x 15 SMD 2835 LED Lamps
- Polycarbonate housing & heads
- Wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 12V 2800mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- Emergency light output - 248 Lumens
- Dimensions - 305 x 306 x 70mm
- Weight - 1.85Kg

Photometric spacing data 1 Lux

Mounting Height	Photometric spacing data 1 Lux	
	Transverse to Wall	Transverse to Transverse
2.5m	5	10
4.0m	5.6	12
6.0m	7.2	14

Calculated with lamp heads fixed at 30° below horizontal