



GUARDCAM WF-T

External Area Protection Camera

Additional transmitter for GuardCam WF systems.

- For use with GuardCam WF system
- 12m 140 degree PIR
- 8W 1100 lumen LED floodlight
- Up to four units per system
- Easy pairing to GuardCam monitor (GuardCam WF-MR) or GuardCam receiver (GuardCam WF-SAR)
- High quality stable images

Detection Method	Passive Infrared
Sensor Range	12m x 140°
Camera Resolution	640 X 480
LED Floodlight output	8Pcs 1W Nichia High Power LED
Lumen output	1100
Time adjustment	5 seconds ~ 10 minutes
Lux adjustment	Dark - daylight
Transmitter signal technology	2.4GHz FHSS Technology
Transmitter output power	16dBm
Transmission Range	150m open field
Voltage	100-240V 50Hz/60Hz
Current drain	225±20mA
IP rating	IP55
Operating Temperature	-10°C ~ 40°C
Dimensions	160 x 176 x 260MM
Weight	1400g

GUARDCAM LED

Combined Security LED Floodlight

GuardCam LED is a complete all-in-one PIR floodlight, camera, speaker and DVR system. Simply connect to mains power, fix to wall, set the time and date and switch on!

- Detect the intruder
- Floodlight the area
- Initiate a high resolution 1080 x 720P video recording
- Deliver an audible warning
- Ability to record users own warning message
- Captures 60,000 still images or 750 twenty second video clips with 4GB card supplied
- Maximum card size allowable now 32GB

Supply Voltage	100-240VAC
Current drain (activated)	0.4amp
Current drain (quiescent)	0.005amp
LED output	1100 Lumens
PIR detection angle	160 deg
PIR detection range	12 metres
Camera exposure control	Automatic
Camera white balance	Automatic
Camera sharpness	Automatic
SD card format	FAT Maximum 32GB
Image Format	JPEG / AVI
IP rating	IP44
Dimensions (mm)	180 x 190 x 315mm
Weight	1.206KG