**Conventional Call Systems** 

Overdoor Light c/w Sounder

## Back to Search results for "NC806CS" (2 other results)



## Overdoor Light c/w Sounder

## Part No. NC806CS

- Provides audible and visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.
- Indicates Standard calls via a constant tone/constant red light and Emergency calls via a pulsing tone/pulsing red light.
- Dual red LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.
- Finished in tough, durable ABS plastic.

- Also available as part of the NC951 Accessible Toilet Alarm kit.
- Stainless steel version also available.

```
CE
```

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls).
Controls	None (the device is controlled by the master calling device it is connected to).
Connections	1 (Signal); -Ve (Negative); +Ve (Positive).
Onboard Sounder	Yes. Sounds constantly for standard calls, intermittently for emergency calls.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	52g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.

Dimensions & Mounting Information

Product dimensions:

87 W x 87 H x 68 D mm. Mounts on a 25mm UK single gang back box.

~

BIM Drawing (REVIT)	
🛓 Download	
CAD Drawing (DWG)	
🕹 Download	
Documentation	^
NCQ06CC Instructions	
NC806CS Instructions	
DNU8060200 Rev 1	
La Download (41.48k)	
3 other products in the same category:	~



## **CONTACT US**

C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.

📞 +44 (0) 1942 322744

⊠ sales@c-tec.co.uk